

PRODUCT-DETAILS

M35/16.P

M35/16.P Screw Clamp Terminal Blocks - Ground - Green-Yellow



| General Information | |
|----------------------------|--|
| Extended Product Type | M35/16.P |
| Product ID | 1SNA165111R1400 |
| EAN | 3472591651119 |
| Catalog Description | M35/16.P Screw Clamp Terminal Blocks - Ground - Green-Yellow |
| Long Description | - Reliable electrical and mechanical contact with the rail, - Flexibility: snap onto symmetrical and asymmetrical rails. |

| Green-Yellow |
|--------------|
| 20 piece |
| 85369010 |
| |

| Popular Downloads | |
|--------------------------------------|-----------------|
| Data Sheet, Technical Information | 1SNC160019C0202 |
| Instructions and Manuals | 1SNC160019C0202 |

| Dimensions | |
|-------------------|-------|
| Product Net Width | 16 mm |

| Product Net Height | 49 mm |
|-------------------------------|---------|
| Product Net Depth / Length | 46.5 mm |
| Product Net Weight | 50.5 g |

| Technical | |
|--|---|
| Rated Cross-Section | 35 mm² |
| Spacing | 16 mm |
| Connection Type | Screw Clamp |
| Function | Ground |
| Number of Levels | 1 |
| Connecting Capacity Main Circuit | Screw Clamp / Flexible 1x 4 35 mm² Screw Clamp / Rigid 1x 4 50 mm² Screw Clamp / With Insulated Ferrrule 1x 35 mm² |
| Gauge Type | B9 |
| Rated Short-time Withstand Current (I _{cw}) | for 1 s 4200 A |
| Dielectric Test Voltage | 3500 V |
| Pollution Degree | 3 |
| Insulation Material | Polyamide |
| Mounting on DIN Rail | G32 (32 \times 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 \times 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 \times 15 mm Mounting Rail) acc. to IEC 60715 |
| Wire Stripping Length | 17.0 mm |
| Recommended Screw Driver | 8 mm |
| Tightening Torque | acc. IEC 60947-1 2.8 N·m Manufacturer 3 N·m |

| Technical UL/CSA | |
|---|---|
| Connecting Capacity Main Circuit UL/CSA | Screw Clamp / Rigid 1x 8 0 AWG |
| Connecting Capacity UL/CSA | Screw Clamp / Rigid 8 0 AWG Stranded 0 AWG |
| Flammability According to UL94 | V-0 |

| Environmental | |
|---------------|---|
| Ambient Air | Operation -55 +110 °C |
| Temperature | Storage -55 +110 °C |
| RoHS Status | Following EU Directive 2002/95/EC August 18, 2005 and amendment |

| Certificates and Declarations (Document Number) | |
|---|-----------------|
| CSA Certificate | 1SND161039A0201 |
| cUL Certificate | 1SND161011A0202 |
| Declaration of Conformity - CE | 1SND225017U1000 |
| EAC Certificate | 1SND161009A1100 |
| Environmental Information | 1SND220004E1002 |
| Instructions and Manuals | 1SNC160019C0202 |
| RMRS Certificate | 1SND161007A1101 |
| RoHS Information | 1SND230023F0208 |

| Classifications | |
|-------------------------------|----------------------------------|
| Object Classification Code | Х |
| ETIM 4 | EC000901 - Ground terminal block |
| ETIM 5 | EC000901 - Ground terminal block |
| ETIM 6 | EC000901 - Ground terminal block |

| Container Information | |
|-----------------------------------|---------------|
| Package Level 1 Units | 20 piece |
| Package Level 1 Width | 81 mm |
| Package Level 1 Depth / Length | 200 mm |
| Package Level 1 Height | 53 mm |
| Package Level 1 Gross Weight | 1.01 kg |
| Package Level 1 EAN | 3472591651119 |
| Package Level 2 Units | 300 piece |
| Package Level 2 Width | 300 mm |
| Package Level 2 Depth / Length | 500 mm |
| Package Level 2 Height | 150 mm |
| Package Level 2 Gross Weight | 15.15 kg |
| Package Level 3 Units | 14400 piece |

Categories

Low Voltage Products and Systems \rightarrow Connection Devices \rightarrow Terminal Blocks \rightarrow SNA Series

