

PICCOLO PC B 85 T



Sample photo

Order symbol: PC B 85 T
Product nbr: 8724004
Description: Enclosure, PC
Remarks: Transparent cover

EAN: 6418074001962
EI. number:
 Finland: 3423503
 Electric No. Denmark: 8212001501
 Electric No. Italy: 7202015
 Electric No. Sweden: 2536835

Including: Base with screws for mounting plate, cover with PUR gasket and polyamide cover screws.

| Dimensions: | Length | Width | Height | Accessories: |
|-------------|--------|-------|--------|--|
| mm: | 110 | 80 | 85 | B-3 FP 22040 |
| inch: | 4.3 | 3.1 | 3.3 | DIN-35 Mounting rail Wall fastening lug (2 pcs) |

| Materials: | Rating: |
|--|--|
| Material: Polycarbonate | Ingress Protection (EN 60529): IP66/IP67 |
| Base colour: RAL 7035 -light grey | Impact Resistance (EN 62262): IK08 |
| Cover screws material: Polyamide | Electrical insulation: Totally insulated |
| Cover colour: Clear transparent | Halogen free (DIN/VDE 0472, Part 815): 1 |
| Cover screws colour: Grey | UV resistance: UL 508 |
| Gasket material: Polyurethane | Flammability Rating: UL 746C 5" |
| | Glow Wire Test (IEC 695-2-1) °C: 960 |
| | NEMA Class: NEMA 1, 4X, 6, 12, 13 |

| Temperatures: | Certificates: |
|--|---------------|
| Temperature °C (short term): -40 ... 120 °C | SGS Fimko |
| Temperature °C (continuous): -40 ... 80 °C | Gost R |
| Temperature °F (short term): -40 ... 250 °F | |
| Temperature °F (continuous): -40 ... 175 °F | |

| Accessories: |
|--|
| B-MP Mounting plate |

