

ENSTO

PRODUCT SPECIFICATION

02/01/2020



6418677191954

Tapping terminal block

KE66.2

Code	KE66.2
GTIN	6418677191954
Name	Tapping terminal block Ensto Clampo Pro Tapping block, blue, Al 6-50 mm ² , Cu 2.5-50 mm ²
Description	Ensto Clampo Pro is a comprehensive universal terminal series for Al/Cu conductors of 2.5 – 240 mm ² .
Vendor	Ensto Finland Oy


Technical specification
Others

ETIM Class: EC000897

Material

Housing: Polyamide

Colors

Color: Blue

Certificates

Connector class: A
 Standards: EN 60947-7-1, UL 1059, EN 61238-1
 UL category: XCFR2
 UL File no.: E192532, E192532

US specific

Maximum voltage: 600 V

Dimensions

Conductor cross-section: Cu 2,5-50 Al 6-50
 Conductor size: 1/0-6
 Dimensions l x w x h: 49 x 29.8 x 43
 Weight: 0.05 kg

Features

Mounting:	DIN rail
Number of poles:	1
Number of termination points:	4
Screw head:	Hexagon
Screw head size:	5 mm

Temperatures

Operating temperature:	≤ 80 °C
------------------------	---------

Mechanical

Tightening torque:	4 Nm (2.5-4mm ²), 12 Nm (6-50mm ²)
--------------------	------------------------------------------------------------

Electrical values

Nominal current:	Cu 160 A, Al 145 A
Nominal insulation voltage:	800 V
Pollution degree:	3

ETIM 7

Etim

Colour:	Blue
Connectable conductor cross section fine-strand with cable end sleeve:	2.5 ... 35 mm ²
Connectable conductor cross section fine-strand without cable end sleeve:	2.5 ... 35 mm ²
Connectable conductor cross section multi-wired:	2.5 ... 50 mm ²
Connection position:	Sideways
Explosion-tested version 'Ex e':	False
Height at lowest possible mounting height:	43 mm
Inflammability class of insulation material acc. with UL94:	V2
Length:	49 mm
Material insulation body:	Thermoplastic
Mounting method:	DIN rail (top hat rail) 35 mm
Number of clamp positions per level:	4
Number of levels:	1
Operation temperature:	-5 ... 80 °C
Rated current I _n :	145 A
Rated voltage:	800 V
Type of electrical connection 1:	Screw connection
Type of electrical connection 2:	Screw connection
Width/grid dimension:	29.8 mm

Packaging

Default package

Unit:	PCE
Package size:	30
Depth:	218 mm
Width:	218 mm
Height:	126 mm
Volume:	5.988024 l