

ENSTO

PRODUCT SPECIFICATION

11/01/2020



6418677171444

Load break switch rotary

KS3.16RY

Code	KS3.16RY
GTIN	6418677171444
Name	Load break switch rotary Ensto Compact 3 x 16 A, yellow with red handle
Description	Ensto Compact is a complete range of rotary switches from 16 A to 125 A.
Vendor	Ensto Finland Oy



Technical specification

Others

ETIM Class: EC000216

Colors

Color: Red-Yellow

Certificates

Standards: EN 60947-3

Short-circuit characteristics

Max. cut-off current: 6 kA
 Max. fuse: 16 A
 Max. Joule integral: 6.8 kA²s
 Rated conditional short-circuit current: 50 kA
 Rated short time withstand current: 1260 A (1 s)

Dimensions

Conductor cross-section: Cu 1.5-16
 Net Weight: 6.7 kg
 Size: 40 x 85 x 79
 Volume : 26.86 cm³
 Weight: 0.13 kg

Mechanical

Tightening torque Nm: 2 Nm

Electrical values

Breaking capacity 415 V, AC 23 A:	128 A
Making capacity 415 V, AC 23 A:	160 A
Rated insulation voltage:	800 V
Rated operational current:	AC 22 A: 415V / 16A, 500V / 16A, 690V / 16A, AC 23 A: 415V / 16A, 500V / 16A, 690V / 16A

ETIM 7

Etim

Colour control element:	Red
Conditioned rated short-circuit current Iq:	50 kA
Device construction:	Complete device in housing
Interlockable:	True
Max. rated operation voltage Ue AC:	690 V
Motor drive integrated:	False
Motor drive optional:	False
Number of poles:	3
Rated operating voltage:	400 ... 690 V
Rated operation power at AC-23 400 V:	7.5 kW
Rated operation power at AC-3 400 V:	8 kW
Rated permanent current at AC-21 400 V:	16 A
Rated short-time withstand current Icw:	1.26 kA
Suitable for distribution board installation:	True
Type of control element:	Short thumb-grip
Type of electrical connection of main circuit:	Screw connection
Version as emergency stop installation:	False
Version as main switch:	True
Version as maintenance-/service switch:	True
Version as reversing switch:	False
Version as safety switch:	False
Voltage release optional:	False

Packaging

Default package

Unit:	PCE
Package size:	50
Weight:	335 kg