

Data sheet

Commercial Art.No.: R1.100.0213.0

Magnet switch set SMA 0213

safety switch and magnet, manipulation safe, rectangle-shaped design, dimensions LxWxH: 88x25x14mm, normally open / normally closed contact, protection category: IP67, cable length: 3m



Commercial Art.No.	R1.100.0213.0
EAN	4049088014536
Order Unit	1

Certificates / Approvals



Technical data

General

Suited for safety functions	yes
Housing material	Plastic
Switching distance	3 mm
Number of protected contact energized outputs	2
Type of electric connection	Cable
Cable length	3 m
Construction type housing	Cuboid
Protected switch distance ON	7 mm
Protected switch distance OFF	17 mm
Cross-/short circuit identification possible	yes
Degree of protection (IP)	IP67
Type of actuation	Magnet

Output circuit

Max. output current at protected output	200 mA
Min. output current	5 mA
Min. rated supply voltage at DC	5 V
Max. rated supply voltage at DC	48 V

Other

Voltage type	DC
Number of protected semiconductor outputs	0
Type of switch output	Other

Dimensions

Width sensor	25 mm
Height of sensor	14 mm

Length of sensor	88 mm
------------------	-------

Classification

ECLASS 11	
ECLASS 8.1	27270105
ETIM 7.0	EC002544
ETIM 6.0	EC002544
ETIM 5.0	EC002544
ETIM 4.0	EC002544

Safety parameters


Category (ISO 13849-1)	4
PL (ISO 13849-1)	Level e
SIL _{Cl} (IEC 62061)	3
HFT	1
T _M	20 a

Product compliance

REACH-SVHC conformity status	Compliant
------------------------------	-----------

Accessories

Commercial Art.No.:	Article-type description:	Description:
R1.100.5004.0	Connection cable M8 SMA 5004	M8 cable female, 4-pole, end cut off, cable length: 5m
R1.100.5005.0	Connection cable M8 SMA 5005	M8 cable female, 4-pole, end cut off, cable length: 10m



Teile-Nr. / Part-No.	Anschluss / connection
R1.100.0213.0	PVC cable - 3 m
R1.100.0223.0	PVC cable - 3 m
R1.100.0224.0	PVC cable - 5 m
R1.100.0226.0	PVC cable - 10 m
R1.100.0228.0	PVC cable - 20 m
R1.100.0233.0	PVC cable - 3 m
R1.100.0236.0	PVC cable - 10 000 m
R1.100.0243.0	PVC cable - 3 m
R1.100.0249.0	M12-8
R1.100.0613.0	PVC cable - 3 m
R1.100.0623.0	PVC cable - 3 m
R1.100.0626.0	PVC cable - 10 m

Weitere Angaben siehe KATALOG oder eKatalog.
Additional data see CATALOG or eCatalog.

www.wieland-electric.com
eshop.wieland-electric.com

ja/yes Stoffverbots- und Deklarationsliste nach WN 5020.010 ist einzuhalten.
Conformity with Wieland document WN 5020.010 e (list of prohibited / declarable hazardous substances) to be declared!

Freitoleranz nach General tolerance	CAD-Zeichnung, keine manuellen Änderungen CAD drawing, no manual modifications allowed	1. Verwendung: First Use:	Blatt: Sheet:
	Werkstoff / Material	2015 Tag/Date	Name
	Maßstab/Scale	gezeichnet drawn 26.05.	Koetzner
		geprüft checked	
		Normgepr. Stand. check	
	Datei / File: 028691_B01K.DCD	Ersatz für / Replacement for:	
⑥ 11.02.20		Type	Benennung / Title
⑤ 11.11.15			Teilespezifikation / Component specification
Index Datum / Blatt Date / Sheet			SMA Magnetschalter rechteckig / Machine safety switch, rectangular
Änderung / Revision			

Zeichnung Nr. / Drawing No.
T R1.100.0213.0 01K

Maße in mm / Dimensions are in mm

wieland
www.wieland-electric.com

Qu - PEE 12/92

A
1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
M1
M2
M3
L
G
i
11.1
12.1
1.1