

ENSTO

Additional pole

KS1.63

Code	KS1.63
GTIN	6418677170089
Name	Additional pole Ensto Compact 63 A, for panel or DIN-rail mounted switch
Description	Accessory for Ensto Compact switches
Vendor	Ensto Building Systems Finland Oy



Technical specification

Certificates

Standards: EN 60947-3

Dimensions

Size: 18 x 56 x 75
 Length: 72 mm
 Volume : 7.56 cm³
 Conductor cross-section: Cu 1.5-16
 Width: 13 mm
 Height: 56 mm
 Net Weight: 0.046 kg

Electrical values

Breaking capacity 415 V, AC 23 A: 504 A
 Making capacity 415 V, AC 23 A: 630 A
 Rated insulation voltage: 800 V
 Rated operational current: AC 22 A: 415V / 63A, 500V / 63A, 690V / 63A,
 AC 23 A: 415V / 63A, 500V / 40A, 690V / 25A

Mechanical

Tightening torque: 2 Nm

Short-circuit characteristics

Max. cut-off current: 6 kA
 Max. fuse: 63 A
 Max. Joule integral: 15 kA²s

Rated conditional short-circuit current: 20 kA
Rated short time withstand current: 1260 A (1 s)

Others

ETIM Class: EC002498

ETIM Technical specification

etim

Type of accessory: 4th pole pole

Packaging

Pallet package

Unit: pcs
Package size: 5250
Depth: 1200 mm
Width: 800 mm
Height: 1032 mm

Default package

Unit: pcs
Package size: 50
Depth: 218 mm
Width: 218 mm
Height: 126 mm
Weight: 2.622 kg
Volume: 5.988024 l