



## Main

Range	ClimaSys
Product name	ClimaSys CV
Product or component type	Fan
Type of filter	Standard
Flow rate	Free flow rate with standard filter: 38 m <sup>3</sup> /h at 50 Hz Free flow rate with standard filter: 39 m <sup>3</sup> /h at 60 Hz
[Us] rated supply voltage	150...250 V
Input voltage	230 V 50/60 Hz

## Complementary

Absorbed power	4.5 W 50 Hz 4.8 W 60 Hz
[In] rated current	0.16 A 50 Hz 0.17 A 60 Hz
Noise level < at	40...41 dB
Bearing type	Ball
Height	137 mm external:
Width	117 mm external:
Depth	49 mm external:
Cut-out dimensions	92 x 92 mm
Net weight	0.22 kg
Material	Outlet grille: injected thermoplastic (ASA PC)
Colour	Outlet grille: grey (RAL 7035)
Ambient air temperature for operation	-10...70 °C
Ambient air temperature for storage	-40...70 °C
Maximum pressure	29 Pa flow rate 0 m <sup>3</sup> /h
Connections - terminals	Cable
IP degree of protection	IP54
Device composition	1 axial motor 2 protective grille: on the front and rear surfaces 1 filter: front of axial motor 1 outlet grille: front 1 cut-out template
Condition of use	Outside temperature must be 5 °C lower than inside temperature Flow rates depends on the work point, see ProClima software Surrounding environment must be relatively clean Filter must be cleaned and replaced regularly Overfrequent filter replacement should be avoided

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes

---

RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

---

### Contractual warranty

---

Warranty	18 months
----------	-----------

---