## **Product datasheet** Characteristics

# NSYS3D121030DP

Spacial S3D dbl plain door with mount.plate. H1200xW1000xD300 IP55 IK10 RAL7035.





#### Main

Mairi		
Range	Spacial	
Product name	Spacial S3D	
Application	Multi-purpose	
Category	Compact enclosure	
Enclosure nominal height	1200 mm	
Enclosure nominal width	1000 mm	
Enclosure nominal depth	300 mm	
Door type	Plain	
Mounting plate description	Plain	
Type of gland plate	Standard	
Installation accessory type	Wall-mounting	
Device composition	1 body 2 cable gland plate 2 door with lock 1 mounting plate	

#### Complementary

		<b>-</b>
Body type	Gutter-shaped front rail double sheet thickness Single piece body	,
Number of doors	Front face: 2 door(s)	
Door opening side	Reversible (120 °)	
Lock type	3 points lock, 3 mm double-bar	to
Accessibility for operation	Front	i
Removable parts	Door by hinges Cable gland plate by screws Mounting plate by fixing element	o documents
Material	Enclosure: steel Mounting plate: galvanised steel	iri F
Surface finish	Enclosure: epoxy-polyester powder	<u>.</u>

Colour	Enclosure: grey (RAL 7035)
Standards	IEC 62208
Product certifications	BV
	DNV
	UL
	GL
	LR
	CUL
Product weight	77 kg

#### Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262

### Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	Download RoHS China Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	

#### Contractual warranty

on the dotter. He had been dearly		
Warranty	18 months	