

Product datasheet

Specifications



Landscape (Horizontal) enclosure polyester monobloc IP66 H536xW747xD300mm

NSYPLM57G

Main

Range	Thalassa
Product name	Thalassa PLM landscape
Device short name	PLM
Enclosure type	Multi-purpose
Category	Compact enclosure
Nominal height	536 mm
Nominal width	747 mm
Nominal depth	300 mm
Enclosure mounting	Wall mounted
Installation direction	Horizontal
Device composition	1 body 1 door 2 lock
Body type	Built-in canopy, on lateral side One piece moulded with notches in the rear
Door type	Plain
Door opening side	Down
Lock type	3 mm double-bar lock

Complementary

Number of locks	2
Mounting plate description	Without mounting plate
Accessibility for operation	Front
Removable parts	Door by cut hinges
Material	Polyester reinforced with fibreglass
Colour	Grey (RAL 7035)
Standards	NEMA classification 13 IEC 62208 NEMA classification 4X
Product certifications	UL BV
Electrical insulation class	Class II

Environment

IP degree of protection	IP66 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262
Fire resistance	960 °C conforming to IEC 62208
Ambient air temperature for operation	-40...80 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	13.88 kg
Package 1 Height	825.5 mm
Package 1 width	558.8 mm
Package 1 Length	342.9 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------