

# PC box IP66 IK08 RAL7035 Int.H225W175D100 Ext.H241W191D128 opaque PC cover H20

Local distributor code: 398324511 NSYTBP241910

| Maır |   |   |   |   |
|------|---|---|---|---|
|      | V | а | ı | r |

| Range               | Thalassa                               |
|---------------------|--|
| Product name        | Thalassa TBP                           |
| Device application  | Multi-purpose                          |
| Category            | Industrial box                         |
| Height              | 241 mm                                 |
| Width               | 194 mm                                 |
| Depth               | 107 mm                                 |
| Internal height     | 225 mm                                 |
| Internal width      | 175 mm                                 |
| Internal depth      | 100 mm                                 |
| Enclosure mounting  | Wall mounted                           |
| Device composition  | 1 body<br>1 cover<br>4 cover screw     |
| Body type           | One piece moulded                      |
| Type of front cover | Low plain cover                        |
| Cover fixing        | Plastic screws                         |
| Lock type           | Captive screw flat outside sealed area |
| Removable parts     | Cover by captive screws                |

#### Complementary

| Material                    | Polycarbonate   |
|-----------------------------|---|
| Colour                      | Grey (RAL 7035)   |
| Standards                   | UL 508 A<br>IEC 62208                                       |
| Product certifications      | TÜV<br>UL   |
| Electrical insulation class | Class II  |
| Mounting location           | Outdoor (with canopy or shelter and anticondensation valve) |
| Net weight                  | 0.72 kg   |
|                             |   |

#### **Environment**

| IP degree of protection             | IP66 conforming to NEMA 4.4X |
|-------------------------------------|------------------------------|
| IK degree of protection             | IK08 conforming to IEC 62262 |
| Fire resistance                     | 960 °C                       |
| Ambient air temperature for storage | -1560 °C                     |
| Operating temperature               | -2580 °C                     |

### **Packing Units**

| PCE     |
|---------|
| 1       |
| 720.0 g |
| 12.8 cm |
| 19.4 cm |
| 24.1 cm |
|         |

### Offer Sustainability

| Sustainable offer status   | Green Premium product  |
|----------------------------|--|
| REACh Regulation           | REACh Declaration  |
| REACh free of SVHC         | Yes  |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration           |
| Toxic heavy metal free     | Yes  |
| Mercury free               | Yes  |
| RoHS exemption information | Yes  |
| China RoHS Regulation      | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |

## Contractual warranty

| Warranty | 18 months |
|----------|-----------|
|----------|-----------|