

Floor standing encl. polyester vers.PLA compl.sealed 1250x750x620 IP65 glazed

NSYPLA1276TG

EAN Code: 3606485434476

Main

Range	Thalassa
Product name	Thalassa PLA
Enclosure type	Multi-purpose
Product or component type	Suitable enclosure
Version	PLA
Nominal height	1250 mm
Nominal width	750 mm
Nominal depth	620 mm
Enclosure mounting	Floor-standing
Device composition	1 top part 1 bottom part 2 side part 1 rear panel 1 door

Complementary

· · · · · · · · · · · · · · · · · ·	
Body type	Sealed top and bottom part assembled with side parts
Door type	Transparent front
Number of doors	1 door(s)
Door opening side	Reversible (120 °)
Lock type	4 points lock, 5 mm double-bar
Accessibility for operation	Rear Front
Removable parts	Door by hinges Rear panel by fixing element
Material	Polyester reinforced with fibreglass
Colour	Grey (RAL 7035)
Standards	UL 508 A IEC 62208
NEMA degree of protection	NEMA 3 NEMA 3S NEMA 13

NEMA 5 NEMA 1 NEMA 12 NEMA 2 NEMA 3X

Product certifications	DNV Marine UL/cUL listed Veritas
Electrical insulation class	Class II

Environment

IP degree of protection	IP65 conforming to IEC 60529 (completely sealed)
IK degree of protection	IK08 conforming to IEC 62262 (glazed door)
Fire resistance	960 °C conforming to IEC 62208
Ambient air temperature for storage	-3590 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	126.0 cm
Package 1 Width	78.0 cm
Package 1 Length	65.0 cm
Package 1 Weight	47.0 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile

Contractual warranty