

## Floor standing encl. polyester vers.PLA compl.sealed 1500x1250x620 IP65 glazed

NSYPLA15126TG

EAN Code: 3606485434506

## Main

Range	Thalassa
Product name	Thalassa PLA
Enclosure type	Multi-purpose
Product or component type	Suitable enclosure
Version	PLA
Nominal height	1500 mm
Nominal width	1250 mm
Nominal depth	620 mm
Enclosure mounting	Floor-standing
Device composition	1 top part 1 bottom part 2 side part 2 door 2 rear panel

## Complementary

Complementary	
Body type	Sealed top and bottom part assembled with side parts
Door type	Transparent front
Number of doors	2 door(s)
Door opening side	Right and left (120 °)
Lock type	4 points lock, 5 mm double-bar
Accessibility for operation	Rear Front
Removable parts	Door by hinges Rear panel by fixing element
Material	Polyester reinforced with fibreglass
Colour	Grey (RAL 7035)
Standards	IEC 62208 UL 508 A
NEMA degree of protection	NEMA 12 NEMA 2 NEMA 13 NEMA 1
Product certifications	UL/cUL listed Veritas

**DNV** Marine

Electrical insulation class	Class II
Environment	
IP degree of protection	IP65 conforming to IEC 60529 (completely sealed)
IK degree of protection	IK08 conforming to IEC 62262 (glazed door)
Fire resistance	960 °C conforming to IEC 62208
Ambient air temperature for storage	-3590 °C
Packing Units	
Unit Type of Package 1	PCE
Package 1 Length	65.0 cm
Number of Units in Package 1	1
Package 1 Width	128.0 cm
Package 1 Height	153.0 cm
Package 1 Weight	97.0 kg
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration

Product out of China RoHS scope. Substance declaration for your information

## **Contractual warranty**

**RoHS** exemption information

China RoHS Regulation

**Environmental Disclosure** 

Mercury free

Warranty 18 months

Yes

Yes

China RoHS declaration

**Product Environmental Profile**