



Sample photo

**Order symbol:** PC 95/75 HG  
**Product nbr:** 6011332  
**Description:** Enclosure, PC  
**Remarks:** Grey cover

**EAN:** 6418074054647  
**EI. number:**  
 Finland 3421366  
 Denmark 8212027734

**Including:** Base with PUR gasket and screws for mounting plate/DIN-rail, cover with polyamide cover screws and wing heads for cover screws.

**Dimensions: L W H Rating:**

<b>mm:</b>	100	100	75
<b>inch:</b>	3.9	3.9	3

**Ingress Protection (EN 60529):** IP 66/67  
**Impact Resistance (EN 50102):** IK 08  
**Electrical insulation:** Totally insulated  
**Halogen free (DIN/VDE 0472, Part 815):** Yes  
**UV resistance:** UL 508  
**Flammability Rating (UL 746 C 5):** UL 94 5V  
**Glow Wire Test (IEC 695-2-1) °C:** 960  
**NEMA Class:** NEMA 1, 4, 4X, 6, 12, 13

**Materials:**

<b>Material:</b>	PC
<b>Base colour:</b>	RAL 7035
<b>Cover colour:</b>	RAL 7035
<b>Cover screws material:</b>	Polyamide
<b>Cover screws colour:</b>	Grey
<b>Gasket material:</b>	Polyurethane

**Certificates:**

**Germanischer Lloyd (GL)**  
**Underwriters Laboratories**  
**Det Norske Veritas**  
**Fimko**  
**Europe EN 50298 1998**  
**UL Canada**  
**Gost R**

**Temperatures:**

<b>Short term:</b>	-40 ... 120 °C
<b>Continuous:</b>	-40 ... 80 °C
<b>Short term:</b>	-40 ... 250 °F
<b>Continuous:</b>	-40 ... 175 °F

**Accessories:**

MIV 95	Mounting plate
B-3	DIN-35 Mounting rail

