

# Product datasheet

Specifications



## Fuse carrier TeSys DF, 2P 32A, fuse size 10x38 mm

Local distributor code: 393394106 DF102

EAN Code : 3389119407236

### Main

Range	TeSys
Product name	TeSys DF
Product or component type	Fuse carrier
Device short name	DF10
Product compatibility	DF2CA fuse cartridge DF2CN fuse cartridge
Poles description	2P
Fuse size	10 x 38 mm
Fuse type	, aM , gG
Control type	Toggle padlockable
Utilisation category	AC-20B conforming to IEC 60947-3 DC-20B conforming to IEC 60947-3
[Ue] rated operational voltage	690 V AC 690 V DC
[Ie] rated operational current	32 A at 400 V AC
[Ith] conventional free air thermal current	32 A 20 °C
[Ui] rated insulation voltage	690 V AC
[Uimp] rated impulse withstand voltage	6 kV
Overtoltage category	III
Short-circuit withstand	120 kA 400 V conforming to IEC 60947-3 120 kA 500 V conforming to IEC 60947-3
Power dissipation in W	3 W maximum power dissipation by fuse

### Complementary

Standards	EN/IEC 60947-3 EN/IEC 60269-2 UL 4248-1 CSA C22.2 No 4248-1 EN 45545-2: R22 HL2
Product certifications	IEC UL recognized CSA CCC EAC DNV-GL

<b>Mounting support</b>	35 mm symmetrical DIN rail
<b>Mounting position</b>	Vertical (tolerance: +/- 23°)
<b>Connections - terminals</b>	Screw clamp terminals 1 cable(s) 1...16 mm <sup>2</sup> rigid Screw clamp terminals 2 cable(s) 1...6 mm <sup>2</sup> rigid Screw clamp terminals 1 cable(s) 1...16 mm <sup>2</sup> flexible with or without Screw clamp terminals 2 cable(s) 1...6 mm <sup>2</sup> flexible with or without
<b>Tightening torque</b>	2.2 N.m - with screwdriver PZ2 2.2 N.m - with screwdriver flat Ø 5.5 mm
<b>Height</b>	79.5 mm
<b>Width</b>	35 mm
<b>Depth</b>	61 mm
<b>Net weight</b>	0.085 kg
<b>Quantity per set</b>	Set of 6

## Environment

<b>Ambient air temperature for storage</b>	-40...70 °C
<b>Ambient air temperature for operation</b>	-40...70 °C with derating above 20°C
<b>Operating altitude</b>	0...2000 m
<b>IP degree of protection</b>	IP20
<b>Pollution degree</b>	3
<b>Fire resistance</b>	960 °C conforming to IEC 60695-2-1
<b>Compatibility code</b>	DF10

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	3.5 cm
<b>Package 1 Width</b>	6.2 cm
<b>Package 1 Length</b>	8 cm
<b>Package 1 Weight</b>	90 g
<b>Unit Type of Package 2</b>	BB1
<b>Number of Units in Package 2</b>	6
<b>Package 2 Height</b>	6.8 cm
<b>Package 2 Width</b>	8.5 cm
<b>Package 2 Length</b>	22.2 cm
<b>Package 2 Weight</b>	566 g
<b>Unit Type of Package 3</b>	S03
<b>Number of Units in Package 3</b>	96
<b>Package 3 Height</b>	30 cm
<b>Package 3 Width</b>	30 cm
<b>Package 3 Length</b>	40 cm
<b>Package 3 Weight</b>	9.66 kg

## Offer Sustainability

<b>Sustainable offer status</b>	Green Premium product
---------------------------------	-----------------------

<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>REACH free of SVHC</b>	Yes
<b>EU RoHS Directive</b>	Compliant <a href="#">EU RoHS Declaration</a>
<b>Toxic heavy metal free</b>	Yes
<b>Mercury free</b>	Yes
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
<b>RoHS exemption information</b>	Yes
<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>
<b>WEEE</b>	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

## Recommended replacement(s)