

Product data sheet

Specifications

Lineryg - additional Neutral bar for screw distri block - 125 A - 12 connections



LGYN12512

Main

Range	Lineryg
Product name	Lineryg DS
Product or component type	Extension module
Comb busbar, distribution terminal block accessory type	Neutral bar
Poles description	1N
Accessory / separate part category	Connection accessories

Complementary

Distribution block outgoers	12 holes
Mounting support	Direct mounting on rear
Mounting mode	By screws
[Ue] rated operational voltage	230 V AC Ph/N
[Ie] rated operational current	125 A at 40 °C
[Ui] rated insulation voltage	500 V AC
[Uimp] rated impulse withstand voltage	8 kV conforming to EN/IEC 61439-1
[Icw] rated short-time withstand current	3.5 kA for 1 s
[Ipk] rated peak withstand current	20 kA
Busbar length	125 mm
9 mm pitches	14
18 mm pitches	7
Height	20 mm
Width	125 mm
Depth	35 mm
Net weight	111 g
Connections - terminals	Supply: screw terminal 1 cable(s) 10...35 mm ² rigid Supply: screw terminal 1 cable(s) 4...25 mm ² flexible with cable end Distribution: screw terminal 7 cable(s) 2.5...25 mm ² rigid Distribution: screw terminal 7 cable(s) 1.5...16 mm ² flexible with cable end Distribution: screw terminal 4 cable(s) 1.5...16 mm ² rigid

Distribution: screw terminal 4 cable(s) 1.5...10 mm² flexible with cable end

Tightening torque	Supply: 2.5 N.m PZ2 screwdriver 9 mm Supply: 2.5 N.m flat screwdriver 9 mm Distribution: 2 N.m PZ2 screwdriver 7.5 mm Distribution: 2 N.m flat screwdriver 7.5 mm Distribution: 2 N.m PZ2 screwdriver 6.5 mm Distribution: 2 N.m flat screwdriver 6.5 mm
--------------------------	---

Range compatibility	ComPact
----------------------------	---------

Environment

Standards	IEC 60947-7-1 IEC 61439-2 EN/IEC 61439-1
------------------	--

Pollution degree	3
-------------------------	---

Overvoltage category	III
-----------------------------	-----

Dielectric strength	2500 V
----------------------------	--------

Ambient air temperature for operation	-25...55 °C
--	-------------

Colour	White (RAL 9003)
---------------	------------------

Packing Units

Unit Type of Package 1	Db
-------------------------------	----

Number of Units in Package 1	1
-------------------------------------	---

Package 1 Height	2 cm
-------------------------	------

Package 1 Width	3.5 cm
------------------------	--------

Package 1 Length	12.5 cm
-------------------------	---------

Package 1 Weight	122 g
-------------------------	-------

Unit Type of Package 2	Doboz
-------------------------------	-------

Number of Units in Package 2	100
-------------------------------------	-----

Package 2 Height	30 cm
-------------------------	-------

Package 2 Width	30 cm
------------------------	-------

Package 2 Length	40 cm
-------------------------	-------

Package 2 Weight	12.832 kg
-------------------------	-----------

Offer Sustainability

REACH Regulation	REACH Declaration
-------------------------	-----------------------------------

REACH free of SVHC	Yes
---------------------------	-----

EU RoHS Directive	Compliant EU RoHS Declaration
--------------------------	--

Toxic heavy metal free	Yes
-------------------------------	-----

Mercury free	Yes
---------------------	-----

China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
------------------------------	---

RoHS exemption information	Yes
-----------------------------------	---------------------

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
-------------	---

Contractual warranty

Warranty	18 months
-----------------	-----------

Recommended replacement(s)