

Product datasheet

Specifications



Spacial S3DB . H250xW300xD150. IP66, IK10, RAL7035. No

Local distributor code: 392986120 NSYS3DB25315

EAN Code : 3606480158827

Main

Range	Spacial
Product name	Spacial S3DB
Application	Terminal application
Category	Compact enclosure
Enclosure nominal height	250 mm
Enclosure nominal width	300 mm
Enclosure nominal depth	150 mm
Door type	Plain
Mounting plate description	Without mounting plate
Type of gland plate	Without gland plate
Installation accessory type	Wall-mounting Horizontal or vertical position
Product destination	For equipping with terminal
Device composition	1 body 1 door 1 lock

Complementary

Body type	Gutter-shaped front rail double sheet thickness Single piece body
Number of doors	Front face: 1 door(s)
Door opening side	Reversible (180 °)
Lock type	3 mm double-bar lock
Accessibility for operation	Front
Removable parts	Door by hinges
Material	Steel
Surface finish	Epoxy-polyester powder
Colour	Grey (RAL 7035)
Standards	IEC 62208
Product certifications	GL BV UL LR cUL

DNV

Net weight 3.374 kg

Environment

NEMA degree of protection NEMA 4X/13

IK degree of protection IK10 conforming to IEC 62262

IP degree of protection IP66 conforming to IEC 60529

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height 19.5 cm

Package 1 Width 26.5 cm

Package 1 Length 31.5 cm

Package 1 Weight 3.374 kg

Unit Type of Package 2 PAM

Number of Units in Package 2 105

Package 2 Height 205.0 cm

Package 2 Width 100.0 cm

Package 2 Length 120.0 cm

Package 2 Weight 367.0 kg

Offer Sustainability

Sustainable offer status Green Premium product

REACH Regulation [REACH Declaration](#)

REACH free of SVHC Yes

EU RoHS Directive Pro-active compliance (Product out of EU RoHS legal scope)
[EU RoHS Declaration](#)

Mercury free Yes

China RoHS Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information

RoHS exemption information Yes

Environmental Disclosure [Product Environmental Profile](#)

Contractual warranty

Warranty 18 months

Recommended replacement(s)