

(!) Discontinued

Powerpact 4 - Molded Case Circuit Breaker - 3P - 40A - 415 V -

Local distributor code: 391524596

MGP0403X

! Discontinued on: 1 Sept 2023

EAN Code: 3606486440865

Main

| Range Of Product | PowerPacT 4 |
|--|---------------------------------|
| Product Or Component Type | Circuit breaker |
| Device Application | Distribution |
| Poles Description | 3P |
| [In] Rated Current | 40 A at 40 °C |
| [Ue] Rated Operational Voltage | 415 V AC 50/60 Hz |
| Suitability For Isolation | Yes conforming to BS EN 60947-2 |
| Utilisation Category | Category A |
| [Icu] Rated Ultimate Short-Circuit Breaking Capacity | 36 kA Icu at 415 V AC 50/60 Hz |
| Trip Unit Name | TM-D |
| Trip Unit Technology | Thermal-magnetic |
| Trip Unit Protection Functions | LI |
| Control Type | Toggle |
| Circuit Breaker Mounting Mode | Panel-mounted |

Complementary

| [Ui] Rated Insulation Voltage | 800 V | |
|--|---|--|
| [Uimp] Rated Impulse Withstand Voltage | 8 kV | |
| [Ics] Rated Service Short-Circuit Breaking Capacity | 36 kA at 415 V AC 50/60 Hz | |
| Mechanical Durability | 50000 cycles | |
| Electrical Durability | 50000 cycles at 440 V In/2 30000 cycles at 440 V In | |
| Mounting Support | Backplate | |
| Mounting Position | Horizontal and vertical | |
| Number Of Modules | 3 module(s)35 mm | |
| Protection Type | L : for overload protection (thermal) I : for short-circuit protection (magnetic) | |
| Trip Unit Rating | 40 A at 40 °C | |
| Thermal Protection Adjustment Range | 2840 A | |
| Earth-Leakage Protection | Without | |

Product Destination 250 A panelboard 400/630 A panelboard

Environment

Standards BS EN 60947-2

Packing Units

Unit Type Of Package 1 PCE

Number Of Units In Package 1

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Learn more >

Well-being performance

| Well-being performance | |
|------------------------|---|
| Reach Free Of Svhc | |
| Mercury Free | |
| Pvc Free | |
| Reach Regulation | REACh Declaration |
| Eu Rohs Directive | Compliant EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |