



# METALCLAD 13A FUSED CONNECTION UNITS

**NORSLO**


- + Robust steel construction
- + Surface and flush mounting options
- + Metal back box supplied as standard




**MCSPU**




**MCSPUN**




**MCSPS**



**MCSPSN**



**MCSPSFO**



**MCSPSFON**

<b>Description</b>	13A Fused Connection Unit	13A Fused Connection Unit, with Neon	13A Switched Fused Connection Unit	13A Switched Fused Connection Unit, with Neon	13A Switched Fused Connection Unit, Flex Outlet	13A Switched Fused Connection Unit, Flex Outlet with Neon
<b>Rating</b>	13 Amp , 250V~50Hz					
<b>Pack Quantity</b>	5					
<b>Barcode</b>	5012739647260	5012739647277	5012739647284	5012739647291	5012739647307	5012739647314
<b>Switch Type</b>	Double Pole					
<b>Terminal Capacity</b>	3 x 2.5mm <sup>2</sup> , 3 x 4.0mm <sup>2</sup> , 2 x 6.0mm <sup>2</sup> ( <b>L&amp;N</b> ) / 3 x 2.5mm <sup>2</sup> , 2 x 4.0mm <sup>2</sup> , 1 x 6.0mm <sup>2</sup> ( <b>Earth</b> )					
<b>Class</b>	Class1 - Front plate must be earthed					
<b>IP Rating</b>	IP2XD					
<b>Ambient Operating Temp</b>	-5° to +40°C					
<b>Fixing Centres</b>	60.3mm					
<b>Knockouts</b>	5					
<b>Flush Mounted Box Depth</b>	25mm					
<b>Back Box Depth</b>	40mm					
<b>Dimensions Plate Thickness L x H x W</b>	81 x 81 x 4mm					
<b>Conforms To</b>	BS 1363					

**TECHNICAL DATA SHEET**

Note: Internal use only

# METALCLAD 13A FUSED CONNECTION UNITS

Wiring Diagram for:-

- MCSPU - 13A Fused Connection Unit
- MCSPUN - 13A Fused Connection Unit, with Neon
- MCSPS - 13A Switched Fused Connection Unit
- MCSPSN - 13A Switched Fused Connection Unit, with Neon
- MCSPSFO - 13A Switched Fused Connection Unit, Flex Outlet
- MCSPSFON - 13A Switched Fused Connection Unit, Flex Outlet with Neon

