

Surface mounting enclosure, Insulated material, With high-grade steel screws, Number of locations 1, 1 x 30.5



**Part no.** M30-FI1  
**197235**  
**EL Number** 4300435  
**(Norway)**

General specifications		
Product name		Eaton Moeller® series M30 Accessory Surface mounting enclosure
Part no.		M30-FI1
EAN		4015080893066
Product Length/Depth		110 millimetre
Product height		44 millimetre
Product width		43 millimetre
Product weight		0.095 kilogram
Certifications		CSA file No. 012528 UL Listed CSA certified UL 508 UL Category Control No.: NKCR CE marking UL File No.: E29184 IEC/EN 60947-5 CSA-C22.2 No. 14-05 CSA Class No.: 3211-03 CSA-C22.2 No. 94-91
Product Tradename		M30
Product Type		Accessory
Product Sub Type		Surface mounting enclosure
Features & Functions		
Enclosure color		Gray
Enclosure material		Plastic
Fitted with:		High-grade steel screws
Knockouts		1 x M20 (cable entry knockout at the side) 1 x M20 (cable entry knockouts at the rear)
Number of locations		1
RAL-number		7035
General information		
Degree of protection		NEMA 4X IP67/IP69K
Opening diameter		30 mm
Communication		
Connection to SmartWire-DT		No
Contacts		
Force for positive opening - min		0 N

### Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Enclosure for control circuit devices (EC000200)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Housing for command and alarm devices (ecl@ss13-27-37-12-05 [AKF023019])		
Number of command positions		1
Construction type housing		Surface mounted housing
Housing material		Plastic
Housing material quality		Other
Diameter openings	mm	30
Colour housing cover		Grey
Degree of protection (IP)		IP67/IP69K
Degree of protection (NEMA)		4X
Width	mm	43

Height	mm	44
Depth	mm	110