

PRODUCT-DETAILS

T16-0.41

T16-0.41 Thermal Overload Relay 0.31 ... 0.41 A



General Information

Extended Product Type	T16-0.41
Product ID	1SAZ711201R1014
EAN	4013614404672
Catalog Description	T16-0.41 Thermal Overload Relay 0.31 ... 0.41 A

Long Description

The T16-0.41 thermal overload relay is an economic electromechanical protection device for the main circuit. It offers reliable and fast protection for motors in the event of overload or phase failure. The device has trip class 10. Further features are the temperature compensation, trip contact (NC), signal contact (NO), automatic- or manual reset selectable, trip-free mechanism, STOP function and a trip indication. The overload relays are connected directly to the mini contactors or block contactors. Single mounting kits are available as accessory.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Data Sheet, Technical Information	2CDC106020D0201
Instructions and	2CDC106019M6802

Manuals

Instructions and Manuals (Part 2)	1SAC200017M0002
Time-Current Characteristic Curve	1SAZ700505F0005
CAD Dimensional Drawing	2CDC001079B0201
Dimension Diagram	1SAZ700404F0001

Dimensions

Product Net Width	45 mm
Product Net Height	76.7 mm
Product Net Depth / Length	53.5 mm
Product Net Weight	0.1 kg

Technical

Setting Range	0.31 ... 0.41 A
Rated Operational Voltage	Auxiliary Circuit 600 V AC/DC Main Circuit 690 V AC
Rated Operational Current (I_e)	0.41 A
Rated Frequency (f)	Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz Auxiliary Circuit DC Main Circuit 50 Hz Main Circuit 60 Hz
Rated Impulse Withstand Voltage (U_{imp})	Auxiliary Circuit 6 kV Main Circuit 6 kV
Rated Insulation Voltage (U_i)	690 V
Number of Poles	3
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	1
Number of Protected Poles	3
Conventional Free-air Thermal Current (I_{th})	Auxiliary Circuit NC 6 A Auxiliary Circuit NO 4 A
Rated Operational Current AC-15 (I_e)	(120 V) NC 3 A (120 V) NO 0.5 A (240 V) NC 3 A (240 V) NO 0.5 A (400 V) NC 0.75 A (400 V) NO 0.5 A (500 V) NC 0.75 A (500 V) NO 0.5 A
Rated Operational Current DC-13 (I_e)	(125 V) NC 0.55 A (125 V) NO 0.55 A (24 V) NC 1.25 A (24 V) NO 1.25 A (250 V) NC 0.27 A (250 V) NO 0.27 A (500 V) NC 0.15 A (500 V) NO 0.15 A (60 V) NC 0.55 A (60 V) NO 0.55 A

Degree of Protection	IP20
Pollution Degree	3
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Flexible 1/2x 0.75 ... 1 mm ² Flexible 1/2x 1 ... 2.5 mm ² Rigid 1/2x 0.75 ... 4 mm ²
Connecting Capacity Main Circuit	Flexible with Ferrule 1/2x 0.75 ... 4 mm ² Flexible with Insulated Ferrule 1/2x 0.75 ... 4 mm ² Flexible 1/2x 0.75 ... 4 mm ² Solid 1/2x 0.75 ... 1.5 mm ² Solid 1/2x 1.5 ... 4 mm ² Stranded 1/2x 1 ... 4 mm ²
Tightening Torque	Auxiliary Circuit 1 ... 1.2 N·m Main Circuit 1.1 ... 1.5 N·m
Wire Stripping Length	Auxiliary Circuit 9 mm Main Circuit 12 mm
Recommended Screw Driver	Main Circuit Pozidriv 2
Power Loss	at Rated Operating Conditions per Pole 1.1 ... 2.0 W
Suitable For	B6 BC6 B7 BC7 VB6 VBC6 VB7 VBC7 MC1 MC2 AS09 AS12 AS16
Standards	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 600 V AC
Contact Rating UL/CSA	(NC:) B600 (NC:) Q600 (NO:) Q600 (NO:) D300
Connecting Capacity Main Circuit UL/CSA	Flexible 1/2x 18-12 AWG Stranded 1/2x 18-10 AWG
Connecting Capacity Auxiliary Circuit UL/CSA	Flexible 1/2x 18-12 AWG Stranded 1/2x 18-12 AWG
Tightening Torque UL/CSA	Auxiliary Circuit 9 ... 11 in·lb Main Circuit 9 ... 13 in·lb

Environmental

Ambient Air Temperature	Operation -25 ... +60 °C Operation Compensated -25 ... +60 °C Storage -50 ... +80 °C
Ambient Air Temperature Compensation	Yes

Maximum Operating Altitude Permissible	2000 m
Resistance to Shock acc. to IEC 60068-2-27	11 ms Pulse 22g
Resistance to Vibrations	3g 3 ... 150 Hz
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006525

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006525
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Eco Transparency

Environmental Information	1SAC200055H0009
---------------------------	-----------------

Certificates and Declarations

ABS Certificate	1SAA941001-0102
BV Certificate	1SAA941001-0203
CB Certificate	1SAA941008-2001
CQC Certificate	CQC2011010309459316
Declaration of Conformity - CCC	2020980304001787
Declaration of Conformity - CE	1SAD101100-3502
Declaration of Conformity - UKCA	1SAD201100-3502
DNV GL Certificate	1SAA941001-0302
EAC Certificate	1SAA941002-2702
GL Certificate	1SAA941007-0401
LR Certificate	1SAA941001-0502
RINA Certificate	1SAA941000-0802
RMRS Certificate	1SAA941000-0704
UL Certificate	E48139-20090126

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	48 mm
Package Level 1 Height	63 mm
Package Level 1 Depth / Length	82 mm
Package Level 1 Gross Weight	0.112 kg

Package Level 1 EAN	4013614404672
Package Level 2 Units	40 piece
Package Level 2 Width	280 mm
Package Level 2 Height	210 mm
Package Level 2 Depth / Length	395 mm
Package Level 2 Gross Weight	8.45 kg
Package Level 2 EAN	4013614440557

Classifications

Object Classification Code	F
ETIM 4	EC000106 - Thermal overload relay
ETIM 5	EC000106 - Thermal overload relay
ETIM 6	EC000106 - Thermal overload relay
ETIM 7	EC000106 - Thermal overload relay
ETIM 8	EC000106 - Thermal overload relay
eClass	V11.0 : 27371501
UNSPSC	39122330
IDEA Granular Category Code (IGCC)	5366 >> Thermal overload relay
E-Number (Finland)	3706137
E-Number (Sweden)	3212058

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
1SAZ701901R0001	DB16 Single Mounting Kit	DB16	1	piece
1SFA616162R1014	KPR3-101L Reset push button	KPR-101L	1	piece

Where Used (as part of "kit")

Identifier	Description	Type
3BHB047970R0001		Kit

Categories

Low Voltage Products and Systems → Control Products → Contactors → Thermal Overload Relays
 Drives → Services → Spares and Consumables → Parts

