

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Product image









Weidmüller's range of products includes end brackets that guarantee a permanent, reliable mounting on the terminal rail and prevent sliding. Versions with and without screws are available. The end brackets include marking options, also for group markers, and also a test plug holder.

General ordering data

Version	End bracket, Wemid, dark beige, Rail: TS 35, when screwed in
Order No.	<u>1059000000</u>
Туре	WEW 35/1
GTIN (EAN)	4008190172282
Qty.	50 pc(s).



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Depth	62.5 mm	Depth (inches)	2.461 inch
Height	56 mm	Height (inches)	2.205 inch
Width	12 mm	Width (inches)	0.472 inch
Vet weight	36.3 g		
Temperatures			
Continuous operating temp., min.	-50 °C	Continuous operating temp., max.	100 °C
Material data			
Material	Wemid	Colour	dark beige
UL 94 flammability rating	V-2	Coloui	uark beige
System specifications			
Version	For the terminals	Rail	TS 35
Additional technical data			
to a more than the second of t	D::	1 . 1 1	
	Direct mounting	Interlock	for screw fixing
	Direct mounting when screwed in	Interlock	for screw fixing
Type of mounting	when screwed in	<u>Interlock</u>	for screw fixing
Type of mounting Conductors for clamping (re	when screwed in	Interlock Tightening torque, min.	for screw fixing
Type of mounting Conductors for clamping (real transfer of the conductors for clamping (real transfer of the conductors)	when screwed in		
Type of mounting Conductors for clamping (r. Tightening torque, max. Dimensions	when screwed in		
Type of mounting Conductors for clamping (r. Tightening torque, max. Dimensions TS 35 offset	when screwed in ated connection) 2.4 Nm		
Type of mounting Conductors for clamping (r. Tightening torque, max. Dimensions TS 35 offset General	when screwed in ated connection) 2.4 Nm		
Type of mounting Conductors for clamping (r. Tightening torque, max. Dimensions TS 35 offset General Installation advice	when screwed in ated connection) 2.4 Nm 28 mm	Tightening torque, min.	1.2 Nm
Type of mounting Conductors for clamping (r. Tightening torque, max. Dimensions TS 35 offset General Installation advice Classifications	when screwed in ated connection) 2.4 Nm 28 mm Direct mounting	Tightening torque, min.	1.2 Nm TS 35
Type of mounting Conductors for clamping (r. Fightening torque, max. Dimensions TS 35 offset General Installation advice Classifications ETIM 6.0	when screwed in ated connection) 2.4 Nm 28 mm Direct mounting	Tightening torque, min. Rail ETIM 7.0	1.2 Nm TS 35 EC001041
Conductors for clamping (r. Fightening torque, max. Dimensions TS 35 offset General Installation advice Classifications ETIM 6.0 ETIM 8.0	when screwed in ated connection) 2.4 Nm 28 mm Direct mounting EC001041 EC001041	Tightening torque, min. Rail ETIM 7.0 ETIM 9.0	1.2 Nm TS 35 EC001041 EC001041
Type of mounting Conductors for clamping (r. Tightening torque, max. Dimensions TS 35 offset General Installation advice Classifications ETIM 6.0 ETIM 8.0 ECLASS 9.0	when screwed in ated connection) 2.4 Nm 28 mm Direct mounting EC001041 EC001041 27-14-11-35	Tightening torque, min. Rail ETIM 7.0 ETIM 9.0 ECLASS 9.1	1.2 Nm TS 35 EC001041 EC001041 27-14-11-35
Installation advice Type of mounting Conductors for clamping (reference of the conductors for clamping (reference of the clamping of the clamping torque, max.) Dimensions TS 35 offset General Installation advice Classifications ETIM 6.0 ETIM 8.0 ECLASS 9.0 ECLASS 10.0 ECLASS 12.0	when screwed in ated connection) 2.4 Nm 28 mm Direct mounting EC001041 EC001041 27-14-11-35 27-14-11-35	Tightening torque, min. Rail ETIM 7.0 ETIM 9.0	1.2 Nm TS 35 EC001041 EC001041
Type of mounting Conductors for clamping (r. Tightening torque, max. Dimensions TS 35 offset General Installation advice Classifications ETIM 6.0 ETIM 8.0 ECLASS 9.0 ECLASS 10.0	when screwed in ated connection) 2.4 Nm 28 mm Direct mounting EC001041 EC001041 27-14-11-35 27-14-11-35 27-14-11-35	Tightening torque, min. Rail ETIM 7.0 ETIM 9.0 ECLASS 9.1 ECLASS 11.0	1.2 Nm TS 35 EC001041 EC001041 27-14-11-35 27-14-11-35

ROHS

Conform



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Downloads

Approval/Certificate/Document of Con-	
formity	Confirmation of Standards EN 45545-2_2020-10
Engineering Data	CAD data – STEP
Engineering Data	Zuken E3.S
User Documentation	<u>StorageConditionsTerminalBlocks</u>
Catalogues	Catalogues in PDF-format
Brochures	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

Blank



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- · Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Type DEK 5/5 MC NE WS
Order No. 1609801044
GTIN (EAN) 4008190397111
Otty. 1,000 pc(s).

Version

Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00

Weidmueller, white

Blank



WS markers are the perfect match for the W-series connectors. Thanks to their system compatibility, the WS tags can also be used with the I-series and the Z-series. The large marking surfaces do not only permit long character strings but also multi-line text. WS markers are ideal for labels with long, customised character strings. Thanks to the proven MultiCard format, printing with PrintJet CONNECT oder/or Plotter is possible.

- Can be fitted in strips or individually
- Markers in proven MultiCard format

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Type WS 12/5 MC NE WS
Order No. 1609860000
GTIN (EAN) 4008190203481
Oty. 720 pc(s).

Version

WS, Terminal marker, 12 x 5 mm, Pitch in mm (P): 5.00 Weidmueller,

Allen-Bradley, white



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

WS 12/5



WS/ DEK

MultiMark terminal markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

Your benefits with MultiMark

- · Firm hold and durable printing
- · Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- · Large label field for optimal legibility
- · High flexibility thanks to manufacturer independence

General ordering data

Type WS 12/5 MM WS
Order No. 2007190000
GTIN (EAN) 4050118392036
Oty. 800 pc(s).

Version

WS, Terminal marker, 12 x 5 mm, Weidmueller, white

SchT group marker carrier



The SchT 5 S group tag carriers are clipped directly onto the TS 32 mounting rail (G-rail) or the TS 35 mounting rail (top-hat rail). It is therefore possible to label the terminal strip irrespective of the terminal and the type of terminal. SchT 5 and SchT 5 S are fitted with ESO 5, STR 5 protective strips.

The SchT 7 is a hinged group tag carrier for inlay tags which enables easy access to the clamping screw. The SchT 7 is fitted with ESO 7, STR 7 protective strips or DEK 5.

Inlay tags and protective strips can be found under "Accessories".

General ordering data

Type SCHT 7
Order No. 0517960000
GTIN (EAN) 4008190001742
Oty. 20 pc(s).

Version

SCHT, Terminal marker, 39.3 x 8 mm, Pitch in mm (P): 7.00

Weidmueller, white



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Accessories

ZGB pivotable group tag holder



The ZGB 15 is a hinged group tag carrier. The tag carrier can hold the dekafix 5, WS 12/5 terminal markers or the inlay tag ESO 15.

The ZGB 30 is a hinged group tag carrier. The tag carrier can hold the dekafix 5, WS 12/5 terminal markers or the inlay tag ESO 7.

Inlay tags and protective strips can be found under "Accessories".

General ordering data

Type	ZGB 15	Version
Order No.	<u>1636530000</u>	Terminal markers, Terminal marker, 15 x 7 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4008190297053	Weidmueller, white
Qty.	20 pc(s).	
Туре	ZGB 30	Version
Type Order No.	ZGB 30 1611930000	Version Terminal markers, Terminal marker, 32 x 7 mm, Pitch in mm (P): 5.00