

Sensor Connector Leads



Technical Datasheet

Key Features

- M12 and M8 connectors moulded to black cable
- IP67 Seal
- PVC and PUR standard range
- Optional other cable types (please contact IMO)
- Jumper leads
- Optional connector with LED indicator
- Quick sensor replacement to reduce down time
- Options with UL/cUL approval



Leads - Options & Ordering Codes

| | | | | | | |
|------------|----------|-----------|----------|-----------|-----------|------------|
| M12 | F | 01 | 3 | 01 | 02 | 000 |
|------------|----------|-----------|----------|-----------|-----------|------------|

| | |
|---------------|------------|
| M12 Connector | M12 |
| M8 Connector | M8 |

| | |
|--------|----------|
| Female | F |
| Male | M |

| | |
|-----------|-----------|
| 90 Degree | 01 |
| In-line | 02 |

| | |
|-----------|------------|
| 02 | 2m Length |
| 03 | 3m Length |
| 05 | 5m Length |
| 10 | 10m Length |

| | |
|-----------|--|
| 01 | PVC/PVC CEI2022 II 0.25 mm ² |
| 02 | PVC/PVC CEI2022 II 0.34 mm ² |
| 03 | PUR/PUR 0.25mm ² |
| 04 | PUR/PUR 0.34mm ² |
| 33 | PUR/PVC 0.34 mm ² Shielded UL/CSA |
| 34 | PUR/PVC 0.25 mm ² Shielded UL/CSA |

*Please contact IMO for full options

| | |
|--------|----------|
| 3 Pole | 3 |
| 4 Pole | 4 |
| 5 Pole | 5 |
| 8 Pole | 8 |

Jumper Leads - Options & Ordering Codes

Please make your selection from the above options (do not include 000), then add suffix from the selection below:

| | | |
|------------|----------|-----------|
| M12 | M | 01 |
|------------|----------|-----------|

| | |
|---------------|------------|
| M12 Connector | M12 |
| M8 Connector | M8 |

| | |
|------|----------|
| Male | M |
|------|----------|

| | |
|-----------|-----------|
| 90 Degree | 01 |
| In-line | 02 |

