




# Data Sheet

## Metric EMC Nickel Plated IP68 Cable Glands – Standard Thread



**Material:** Nickel Plated Brass

**Claw:** PA

**Sealing and sealing ring:** NBR

**Approvals:** CE, RoHS, REACH

**Protection degree:** IP68

**Temperature resistance:** -40°C to 100°C, short time to 120°C

Part Number	Thread AG (mm)	Cable Range (mm)	Mounting Hole (mm)	Thread Length GL (mm)	Joint Length H (mm)	Spanner Size (mm)
IP68M12/EMC	12	3-6.5	12-12.2	7	19	14
IP68M16/EMC	16	4-8.0	16-16.2	8	20	18
IP68M20/EMC	20	6-12.0	20-20.2	8	22	22
IP68M25/EMC	25	10-14.0	25-25.2	9	25	24/27
IP68M25L/EMC	25	13-18.0	25-25.2	9	27	30/27
IP68M32/EMC	32	15-22	32-32.2	10	29	35
IP68M40/EMC	40	18-25	40-40.2	11	35	45
IP68M40L/EMC	40	22-30	40-40.2	11	35	45
IP68M50/EMC	50	32-38	50-50.2	12	37	50/55
IP68M63/EMC	63	37-44	63-63.2	13	38	64/68