

PRODUCT-DETAILS

## C13 110-101

## , Energy meter'Steel', None, Three-phase, 5 A



General Information	
Extended Product Type	C13 110-101
Product ID	2CMA103574R1000
EAN	7392696035743
Catalog Description	, Energy meter'Steel', None, Three-phase, 5 A
Long Description  Eco Transparency	Basic compact meters for use in residential applications for single or multi family houses or in stand alone applications. To be used in a four wire system. The meter has instrumentation values. Three phase direct connected for active energy. One output for pulses or alarm etc. Accuracy class 1.0 (or B for MID meters). The meters is IEC approved + MID approved and verified. 1000 imp/kWh.
Environmental Product	9AKK108467A4138
Declaration - EPD	
Technical	

Function

Electricity meter

© 2024 ABB. All rights reserved.

2024/09/25

Subject to change without notice

Sub-Function	Steel
Rated Voltage (U <sub>r</sub> )	3x220-240 V
Voltage Range	3x176276 V
Rated Current (I <sub>n</sub> )	5 A Maximum 40 A
Current Rating	5 A
Rated Frequency (f)	50 / 60 Hz
	0.72 W
Power Loss	0.64 W
Communication Interface	None
Accuracy	Active Energy Class B MID (±1%)
Measuring Instrument Conformity	Measurement Instrument Directive (MID)
Meter Tariff Rating	One-Tariff
Pulse Output Rate	1000
Number of Poles	4
Number of Phases	Three-phase
Number of Counter Positions	7
Number of Digital In/Outputs	1 DO
Meter Type	Direct connected
Mounting Type	DIN-Rail
Pulse Output Type	Electrical
Type of Indicator	Digital
Enclosure Material	Polycarbonate in transparent front glass and terminal cover. Glass reinforced polycarbonate in housing.
I/O Option	1 digital output

Material Compliance			
RoHS Information	2CMC486006		
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment		
RoHS Date	2011-44		
REACH Declaration	9AKK108467A9482		
REACH Information	True - contains substances > 0.1 mass percentage		
REACH Date	20240429		
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363		
Environmental			
Ambient Air Temperature	Operation -25 70 °C		

Dimensions	
Width in Number of Modular Spacings	3
Product Net Width	54 mm
Product Net Height	26.5 mm
Product Net Depth /	65 mm

© 2024 ABB. All rights reserved.

Degree of Protection

2024/09/25

Subject to change without notice

IP20

Length	
Product Net Weight	0.170 kg
Dimension Diagram	2CMC486004M0201

Ordering	
Package Level 1 Units	box 1 piec
Package Level 1 Gross Weight	2288 -
E-Number (Finland)	670106
Certificates and Declarations	
Declaration of Conformity - CE	2CMC486004D000
Installation	
Instructions and Manuals	2CMC486006M020
Popular Downloads	
Popular Downloads Data Sheet, Technical Information	2CMC486004M020
Data Sheet, Technical	2CMC486004M020
Data Sheet, Technical Information Classifications	2CMC486004M020 EC001506 - Kilowatt-hour mete
Data Sheet, Technical Information Classifications ETIM 8	
Data Sheet, Technical Information Classifications ETIM 8 ETIM 9	EC001506 - Kilowatt-hour mete
Data Sheet, Technical Information Classifications ETIM 8 ETIM 9 WEEE Category	EC001506 - Kilowatt-hour mete EC001506 - Kilowatt-hour mete
Data Sheet, Technical Information Classifications ETIM 8 ETIM 9 WEEE Category WEEE B2C / B2B	EC001506 - Kilowatt-hour mete EC001506 - Kilowatt-hour mete 5. Small Equipment (No External Dimension More Than 50 cm Business To Consume
Data Sheet, Technical Information	EC001506 - Kilowatt-hour mete EC001506 - Kilowatt-hour mete 5. Small Equipment (No External Dimension More Than 50 cm

Accessories						
Identifier	Description	Type Quantity		Unit Of Measure		
2CCG000242R0001	Control unit	SCU100	1	piece		
2CDG110226R0011	Energy Management	QA/S3.16.1	1	piece		
2CDG110227R0011	Energy Management	QA/S3.64.1	1	piece		

## Categories

Low Voltage Products and Systems  $\rightarrow$  Modular DIN Rail Products  $\rightarrow$  Energy Efficiency Devices  $\rightarrow$  Energy Meters









3605