

PCB PLAIN COPPER BUSBAR



CERTIFICATIONS



FEATURES

Heavy-duty power connection

Circuit breaker, generator and prefabricated power network conductor

Alternative to large and multiple cables

Earth/ground connection

Power distribution

Rounded edges

SPECIFICATIONS


Material: Copper

Table 1/1

| Catalog Number | Article Number | Width (W) | Thickness (T) | Length (L) | Unit Weight |
|----------------|----------------|-----------|---------------|------------|-------------|
| PCB-1M-12X4 | 550780 | 12 mm | 4 mm | 1000 mm | 0.43 kg |
| PCB-2M-12X4 | 550790 | 12 mm | 4 mm | 2000 mm | 0.85 kg |
| PCB-2M-100X5 | 549640 | 100 mm | 5 mm | 2000 mm | 8.9 kg |
| PCB-2M-12X5 | 550770 | 12 mm | 5 mm | 2000 mm | 1.06 kg |
| PCB-2M-25X5 | 549600 | 25 mm | 5 mm | 2000 mm | 2.2 kg |
| PCB-2M-50X5 | 549610 | 50 mm | 5 mm | 2000 mm | 4.5 kg |
| PCB-2M-63X5 | 549620 | 63 mm | 5 mm | 2000 mm | 5.6 kg |

| CatalogNumber | Article Number | Width (W) | Thickness (T) | Length (L) | Unit Weight |
|---------------|----------------|-----------|---------------|------------|-------------|
| PCB-2M-80X5 | 549630 | 80 mm | 5 mm | 2000 mm | 7.1 kg |
| PCB-4M-100X5 | 550670 | 100 mm | 5 mm | 4000 mm | 17.8 kg |
| PCB-4M-20X5 | 550600 | 20 mm | 5 mm | 4000 mm | 3.56 kg |
| PCB-4M-25X5 | 550610 | 25 mm | 5 mm | 4000 mm | 4.45 kg |
| PCB-4M-30X5 | 550620 | 30 mm | 5 mm | 4000 mm | 5.34 kg |
| PCB-4M-40X5 | 550630 | 40 mm | 5 mm | 4000 mm | 7.12 kg |
| PCB-4M-50X5 | 550640 | 50 mm | 5 mm | 4000 mm | 8.9 kg |
| PCB-4M-60X5 | 550650 | 60 mm | 5 mm | 4000 mm | 10.68 kg |
| PCB-4M-80X5 | 550660 | 80 mm | 5 mm | 4000 mm | 14.24 kg |
| PCB-2M-100X10 | 549750 | 100 mm | 10 mm | 2000 mm | 17.8 kg |
| PCB-2M-120X10 | 549760 | 120 mm | 10 mm | 2000 mm | 21.4 kg |
| PCB-2M-30X10 | 549700 | 30 mm | 10 mm | 2000 mm | 5.3 kg |
| PCB-2M-40X10 | 549710 | 40 mm | 10 mm | 2000 mm | 7.1 kg |
| PCB-2M-50X10 | 549720 | 50 mm | 10 mm | 2000 mm | 8.9 kg |
| PCB-2M-60X10 | 549730 | 60 mm | 10 mm | 2000 mm | 10.7 kg |
| PCB-2M-80X10 | 549740 | 80 mm | 10 mm | 2000 mm | 14.2 kg |
| PCB-4M-100X10 | 550930 | 100 mm | 10 mm | 4000 mm | 35.6 kg |
| PCB-4M-120X10 | 550940 | 120 mm | 10 mm | 4000 mm | 42.8 kg |
| PCB-4M-160X10 | 550950 | 160 mm | 10 mm | 4000 mm | 57 kg |
| PCB-4M-30X10 | 550970 | 30 mm | 10 mm | 4000 mm | 10.69 kg |
| PCB-4M-40X10 | 550980 | 40 mm | 10 mm | 4000 mm | 14.25 kg |
| PCB-4M-50X10 | 550900 | 50 mm | 10 mm | 4000 mm | 17.8 kg |
| PCB-4M-60X10 | 550910 | 60 mm | 10 mm | 4000 mm | 21.35 kg |
| PCB-4M-80X10 | 550920 | 80 mm | 10 mm | 4000 mm | 28.5 kg |

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America
+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

Europe
Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europe
Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC
Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF
TRACER