


PRODUCT-DETAILS

OS20FB12A1-2

OS20FB12A1-2 Switch Fuse



General Information

Extended Product Type	OS20FB12A1-2
Product ID	1SCA108791R1001
EAN	6417019420356
Catalog Description	OS20FB12A1-2 Switch Fuse
Long Description	Switch Fuses,Front Operated,3-pole,12 (Between the Poles),British Standard,,Handle and shaft not included,

Popular Downloads

Instructions and Manuals	1SCC311030M0202
--------------------------	-----------------

Dimensions

Product Net Weight	0.63 kg
--------------------	---------

Technical

Rated Operational Current AC-21A (I_e)	(690 V) 20 A (690 V) 380415V;20 A (690 V) 500V;20 A
Conventional Free-air Thermal Current (I_{th})	q = 40 °C 20 A

Conventional Thermal Current (I_{the})	Fully Enclosed 20 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	690 V AC
Rated Conditional Short-Circuit Current (I_{nc})	(690 V) 80 kA
Handle Type	Handle and shaft not included
Switches Operating Mechanism	12 (Between the Poles)
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Fuse Size	A1
Fuse System	British Standard
Operating Mode	Front Operated
Mounting Type	Base mounting
Number of Poles	3

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC311129D2702
DNV GL Certificate	1SCC311125D0203
EAC Certificate	EAC OT_OTDC_OTL_OTP_OTR_OTU_OTE_OETL_OESA_OESC_OTM_OS_OSM_p f
Instructions and Manuals	1SCC311030M0202
RoHS Information	1SCC311106D0203

Container Information

Package Level 1 EAN	6417019420356
---------------------	---------------

Classifications

ETIM 5	EC001040 - Fuse switch disconnecter
ETIM 6	EC001040 - Fuse switch disconnecter
ETIM 7	EC001040 - Fuse switch disconnecter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → Switch Fuses

