

PRODUCT-DETAILS

# OT125FT3

## OT125FT3 SWITCH-DISCONNECTOR



### General Information

Extended Product Type	OT125FT3
Product ID	1SCA105060R1001
EAN	6417019391908
Catalog Description	OT125FT3 SWITCH-DISCONNECTOR
Long Description	3-pole, front operated, door mounted, switch-diconnector / non-fusible diconnect switch with front protected clamp terminals, handle and shaft are not included

### Popular Downloads

Data Sheet, Technical Information	1SCC301020C0201
Instructions and Manuals	1SCC301057M0007
Mechanical Drawings	1SCC301470F0001 1SCC301469F0001 OT125FT3.igs

### Dimensions

Product Net Width	70 mm
Product Net Height	100 mm
Product Net Depth / Length	66.5 mm
Product Net Weight	0.42 kg

## Technical

Rated Operational Current AC-21A ( $I_e$ )	(380 ... 415 V) 125 A (500 V) 125 A (690 V) 125 A
Rated Operational Current AC-22A ( $I_e$ )	(380 ... 415 V) 125 A (500 V) 125 A (690 V) 125 A
Rated Operational Current AC-23A ( $I_e$ )	(380 ... 415 V) 90 A (500 V) 70 A (690 V) 50 A
Rated Operational Power AC-23A ( $P_e$ )	(220 ... 240 V) 22 kW (400 ... 415 V) 45 kW (500 V) 45 kW (690 V) 45 kW
Conventional Free-air Thermal Current ( $I_{th}$ )	q = 40 °C 125 A
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 125 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	8 kV
Rated Insulation Voltage ( $U_i$ )	acc. to IEC/EN 60664-1 750 V
Rated Operational Voltage	Main Circuit 750 V
Rated Short-Circuit Making Capacity ( $I_{cm}$ )	(690 V) 3.6 kA
Rated Short-time Withstand Current ( $I_{cw}$ )	for 1 s 2.5 kA
Power Loss	at Rated Operating Conditions per Pole 6.3 W
Pollution Degree	3
Handle Type	Handle and shaft not included
Switches Operating Mechanism	Mechanism on Top of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front operated
Standards	IEC 60947-3
Special Functions	No
Mounting Type	Door mounting
Number of Poles	3
Cable Cross-Section	Cu 10...70 mm <sup>2</sup>
Degree of Protection	Front IP20
Terminal Type	Screw Terminals
Tightening Torque	acc. IEC 60947-1 6 N·m
Mechanical Durability	20000

## Technical UL/CSA

Maximum Operating Voltage UL/CSA	600 V
Horsepower Rating UL/CSA	(acc. to UL 200 V) 25 Hp (acc. to UL 480 V) 50 Hp (acc. to UL 240 V) 30 Hp (acc. to UL 208 V) 25 Hp (acc. to UL 600 V) 50 Hp
Ampere Rating UL/CSA	100 A

---

## Environmental

---

RoHS Status	Following EU Directive 2011/65/EU
Environmental Information	1SCC301183D0201

---



---

## Certificates and Declarations (Document Number)

---

Declaration of Conformity - CE	1SCC301168D2702
Environmental Information	1SCC301183D0201
Instructions and Manuals	1SCC301057M0007
RoHS Information	1SCC301183D0202

---



---

## Container Information

---

Package Level 1 Units	1 piece
Package Level 1 Width	81 mm
Package Level 1 Depth / Length	112 mm
Package Level 1 Height	79 mm
Package Level 1 Gross Weight	0.44 kg
Package Level 1 EAN	6417019391908

---



---

## Classifications

---

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
UNSPSC	39122233
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Sweden)	3170950

---



---

## Categories

---

Low Voltage Products and Systems → Switches → Switch Disconnectors

