



Sample photo

**Order symbol:** CAB PC 203018 G  
**Product nbr:** 8113331

**Description:** Cabinet, PC  
**Remarks:** Latches on the short side, smooth

**EAN:** 6418074020024  
**EI. number:**  
 Finland 3424103  
 Denmark 8212020401  
 Italy 7821010  
 Sweden 2539963

**Including:** Cabinet base, door with EPDM gasket, latches, screws for mounting plate/DIN-rail and corner plugs.

Dimensions:		L	W	H	Rating:
mm:		200	300	180	<b>Ingress Protection (EN 60529):</b> IP 65
inch:		7.9	11.8	7.1	<b>Impact Resistance (EN 50102):</b> IK 08
Materials:					
<b>Material:</b>		PC			
<b>Base colour:</b>		RAL 7035			
<b>Cover colour:</b>		RAL 7035			
<b>Gasket material:</b>		EPDM			
Temperatures:					
<b>Short term:</b>		-40 ... 120 °C			
<b>Continuous:</b>		-40 ... 80 °C			
<b>Short term:</b>		-40 ... 250 °F			
<b>Continuous:</b>		-40 ... 175 °F			
Accessories:					
EKIV 23		Mounting plate			
EKIV 17		DIN-35 Mounting rail			
EKIV 27		DIN-35 Mounting rail			
FP A 23		Swing-out door, aluminium			
FP 23		Front plate			
FP 12-23		Front Plate			
DRF 23		DIN rail frame set			
DRF 33		DIN rail frame set			
Certificates:					
		Germanischer Lloyd (GL)			
		Underwriters Laboratories			
		Fimko			
		Lloyds Register of Shipping (LR)			
		Europe EN 50298 1998			
		UL Canada			
		Gost R			
		Electrical insulation: Totally insulated			
		Halogen free (DIN/VDE 0472, Part 815): Yes			
		UV resistance: UL 508			
		Flammability Rating (UL 746 C 5): UL 94 5V			
		Glow Wire Test (IEC 695-2-1) °C: 960			
		UL Type: UL TYPE 1, 4, 4X, 12, 13			

