FIBOX CAB CAB PC 403018 G

Sample photo

Order symbol: CAB PC 403018 G
Product nbr: 8113350

Description: Cabinet, PC
Remarks: Latches on the long side, smooth

EAN:	6418074020208
El. number:	
Finland	3424114
Denmark	8212020249
Italy	7821040
Sweden	2539971

Including: Cabinet base, door with EPDM gasket, latches, screws for mounting plate/DIN-rail and corner plugs.

Dimensions:	**L**	**W**	**H**
mm:	400	300	180
inch:	15.7	11.8	7.1

Materials:

Material: PC
Base colour: RAL 7035
Cover colour: RAL 7035
Gasket material: EPDM

Temperatures:

Short term: -40 … 120 °C
Continuous: -40 … 80 °C
Short term: -40 … 250 °F
Continuous: -40 … 175 °F

Accessories:

EKIV 43	Mounting plate
EKIV 27	DIN-35 Mounting rail
EKIV 37	DIN-35 Mounting rail
FP A 43	Swing-out door, aluminium
FP 43	Front plate
FP 12x2-43	Front Plate
FP 12x3-43	Front Plate
DRF 43/44	DIN rail frame set

Rating:

Ingress Protection (EN 60529): IP 65
Impact Resistance (EN 50102): IK 08
Electrical insulation: Totally insulated
Halogen free (DIN/VDE 0472, Part 815): Yes
UV resistance: UL 508
Flammability Rating (UL 746 C 5): UL 94 5V
Glow Wire Test (IEC 695-2-1) °C: 960
UL Type: UL TYPE 1, 4, 4X, 12, 13

Certificates:

Germanischer Lloyd (GL)
Underwriters Laboratories
Fimko
Lloyds Register of Shipping (LR)
Europe EN 50298 1998
UL Canada
Gost R



(c) Fibox OY, Data subject to change without notice