



Sample photo

Order symbol: CAB PC 403018 T
Product nbr: 8113050
Description: Cabinet, PC
Remarks: Latches on the long side, smooth

EAN: 6418074020215
EI. number:
 Finland 3424164
 Denmark 8212020252
 Italy 7822040
 Sweden 2539945

Including: Cabinet base, door with EPDM gasket, latches, screws for mounting plate/DIN-rail and corner plugs.

Dimensions:	L	W	H
mm:	400	300	180
inch:	15.7	11.8	7.1

Materials:	
Material:	PC
Base colour:	RAL 7035
Cover colour:	Smoked grey
Gasket material:	EPDM

Temperatures:	
Short term:	-40 ... 120 °C
Continuous:	-40 ... 80 °C
Short term:	-40 ... 250 °F
Continuous:	-40 ... 175 °F

Accessories:	
EKIV 43	Mounting plate
EKIV 27	DIN-35 Mounting rail
EKIV 37	DIN-35 Mounting rail
FP A 43	Swing-out door, aluminium
FP 43	Front plate
FP 12x2-43	Front Plate
FP 12x3-43	Front Plate
DRF 43/44	DIN rail frame set

Rating:
Ingress Protection (EN 60529): IP 65
Impact Resistance (EN 50102): IK 08
Electrical insulation: Totally insulated
Halogen free (DIN/VDE 0472, Part 815): Yes
UV resistance: UL 508
Flammability Rating (UL 746 C 5): UL 94 5V
Glow Wire Test (IEC 695-2-1) °C: 960
UL Type: UL TYPE 1, 4, 4X, 12, 13

Certificates:
Germanischer Lloyd (GL)
Underwriters Laboratories
Fimko
Lloyds Register of Shipping (LR)
Europe EN 50298 1998
UL Canada
Gost R

