



Sample photo

Order symbol: CAB PC 405020 T
Product nbr: 8113061
Description: Cabinet, PC
Remarks: Latches on the short side, smooth

EAN: 6418074020352
EI. number:
 Finland 3424172
 Denmark 8212020456
 Italy 7822050
 Sweden 2539953

Including: Cabinet base, door with EPDM gasket, latches, screws for mounting plate/DIN-rail and corner plugs.

Dimensions:			L		W		H		Rating:		
mm:	400	500	200					Ingress Protection (EN 60529): IP 65			
inch:	15.7	19.7	7.9					Impact Resistance (EN 50102): IK 08			
Materials:			Electrical insulation: Totally insulated								
Material:	PC		Halogen free (DIN/VDE 0472, Part 815): Yes								
Base colour:	RAL 7035		UV resistance: UL 508								
Cover colour:	Smoked grey		Flammability Rating (UL 746 C 5): UL 94 5V								
Gasket material:	EPDM		Glow Wire Test (IEC 695-2-1) °C: 960								
Temperatures:			Certificates:								
Short term:	-40 ... 120 °C		Germanischer Lloyd (GL)								
Continuous:	-40 ... 80 °C		Underwriters Laboratories								
Short term:	-40 ... 250 °F		Fimko								
Continuous:	-40 ... 175 °F		Lloyds Register of Shipping (LR)								
Accessories:			Europe EN 50298 1998								
EKIV 54	Mounting plate		UL Canada								
EKIV 37	DIN-35 Mounting rail		Gost R								
EKIV 47	DIN-35 Mounting rail										
FP A 54	Swing-out door, aluminium										
FP 54	Front plate										
FP 18X2-54	Front Plate										
DRF 54	DIN rail frame set										

