



Main

Range	ClimaSys
Product name	ClimaSys CV
Product or component type	Fan
Range compatibility	P G
Type of filter	Standard
Flow rate	Free flow rate with standard filter: 562 m ³ /h at 50 Hz Free flow rate with standard filter: 586 m ³ /h at 60 Hz
[Us] rated supply voltage	207...244 V
Input voltage	230 V 50/60 Hz

Complementary

Absorbed power	68 W 50 Hz 85 W 60 Hz
[In] rated current	0.52 A 50 Hz 0.37 A 60 Hz
Noise level < at	59 dB
Bearing type	Ball
Height	336 mm external:
Width	316 mm external:
Depth	161 mm external:
Cut-out dimensions	291 x 291 mm
Net weight	3.2 kg
Material	Outlet grille: injected thermoplastic (ASA PC)
Colour	Outlet grille: grey (RAL 7035)
Ambient air temperature for operation	-15...60 °C
Ambient air temperature for storage	-40...70 °C
Maximum pressure	140 Pa flow rate 0 m ³ /h
Connections - terminals	Terminal block
IP degree of protection	IP54
Device composition	1 axial motor 2 protective grille: on the front and rear surfaces 1 filter: front of axial motor 1 outlet grille: front 1 cut-out template
Condition of use	Filter must be cleaned and replaced regularly Surrounding environment must be relatively clean Outside temperature must be 5 °C lower than inside temperature Overfrequent filter replacement should be avoided Flow rates depends on the work point, see ProClima software

Offer Sustainability

RECh Regulation	RECh Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------
