



Main

| | |
|-------------------------------------|---|
| Device application | Distribution |
| Range | Easy9 |
| Product or component type | Residual current breaker with overcurrent protection (RCBO) |
| Device short name | Easy9 RCBO |
| Poles | 1P + Ns |
| Neutral position | Left |
| [In] rated current | 32 A |
| Earthing system | TN |
| Network type | AC |
| Trip unit technology | Thermal-magnetic |
| Curve code | B |
| Earth-leakage sensitivity | 30 mA |
| Earth-leakage protection time delay | Instantaneous |
| Earth-leakage protection class | Type A |
| Breaking capacity | 6000 A Icn at 230 V AC 50 Hz conforming to BS EN 61009-1 |

Complementary

| | |
|--|---|
| Device location in system | Outgoer |
| Network frequency | 50 Hz |
| [Ue] rated operational voltage | 230 V AC 50 Hz |
| Magnetic tripping limit | 3...5 x In |
| Residual current tripping technology | Voltage dependent functional earth |
| Limitation class | 3 |
| [Ui] rated insulation voltage | 500 V |
| [Uimp] rated impulse withstand voltage | 4 kV |
| Surge current | 250 A |
| Contact position indicator | Yes |
| Control type | Toggle |
| Mounting support | DIN rail |
| 9 mm pitches | 2 |
| Height | 110 mm |
| Width | 18 mm |
| Depth | 72 mm |
| Net weight | 180 g |
| Colour | Grey (RAL 7035) |
| Mechanical durability | 10000 cycles |
| Electrical durability | 4000 cycles 230 V AC 50 Hz |
| Connections - terminals | Tunnel type terminal (top) 25 mm ² rigid Tunnel type terminal (bottom) 16 mm ² rigid Tunnel type terminal (bottom) 16 mm ² flexible Cable (top) 2 cable(s) flexible |
| Tightening torque | 2 N.m top or bottom |
| Earth-leakage protection | Integrated |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

| | |
|---------------------------------------|---------------|
| Standards | BS EN 61009-1 |
| Product certifications | CE |
| Overvoltage category | IV |
| Tropicalisation | 2 |
| Relative humidity | 95 % at 55 °C |
| Ambient air temperature for operation | -15...60 °C |
| Ambient air temperature for storage | -40...85 °C |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |