



### Main

Range	Easy9
Product or component type	Empty consumer unit
Enclosure type	Metal enclosure
Number of 18 mm modules per row	6
Provided equipment	Earth/Neutral terminal block busbar

### Complementary

Enclosure mounting	Surface
Total number of 18 mm modules	6
Number of horizontal rows	1
Number of ways	6 ways
Enclosure material	Metal
Type of front cover	Plain
[In] rated current	100 A
[Ue] rated operational voltage	230/240 V
Network frequency	50 Hz
Type of rail	DIN
Cable entry	Knock-out
Cable cross section	1...25 mm <sup>2</sup> incoming
Comb busbar and distribution block compatibility	YES
Net weight	4.295 kg
Height	276.8 mm
Width	284.8 mm
Depth	119.55 mm
Colour	White (RAL 9003)
Product compatibility	Easy9 RCCB Easy9 MCB Easy9 switch Easy9 SPD Easy9 RCBO

### Environment

Standards	BS EN 61439-3 BS 7671:amendment 3
IP degree of protection	IPxx D (on top) IP3x (with cover)
IK degree of protection	IK05
Overvoltage category	II

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations