

Operating temperature °F:	-40 ... 176 °F
Short term temperature range °F:	-40 ... 248 °F
Size inch:	8.78 x 8.03 x 5.27 in
Weight pound:	2.46 lb
Width inch:	8.03 in

Ratings

Flammability rating:	UL 746C 5 inch flame test
Rated voltage:	1000 ... 1500 V

Material

Gasket:	Polyurethane
Material selection:	Polycarbonate

Mechanical

Impact strength:	IK10 +40C° / -35C°
------------------	--------------------

Technical information

Material:	Polycarbonate
-----------	---------------

Certificates

Standards:	UL 508A
------------	---------

ETIM

Etim

Colour:	Grey
Degree of protection (NEMA):	6P
Depth:	134 mm
EMC-version:	False
Floor installation possible:	False
Height:	223 mm
Impact strength:	IK10
Material:	Plastic
Material quality:	Other
Mounting plate depth-adjustable:	True
Number of doors:	1
Pitched roof:	False
Pole fastening:	True
RAL-number:	7035
Suitable for metrical mounting:	False
Suitable for outdoor set-up:	True
Surface finishing:	Untreated
Tackable:	False
Wall build in:	False
Wall fastening possible:	True
With backside door:	False

With glazed door:	False
With mounting plate:	False
With ventilation door:	False

Packaging

Default package

Unit:	PCE
Package size:	1
Depth:	229 mm
Width:	229 mm
Height:	148 mm
Weight:	1.24 kg
Volume:	7.76 l