



### Main

Range of product	Exclusive
Aesthetic name	Square edge white moulded
Product or component type	Socket-outlet with residual current device
Device presentation	Complete product
Colour tint	White
Quantity per set	Set of 1




### Complementary

Rated current	13 A at 230 V AC
Residual current	30 mA
Number of gangs	2 gangs
Fixing mode	By screws
Connections - terminals	Screw terminals
Material	Urea (carbamide)
Type of installation	Indoor
Depth	43 mm
Width	146 mm
Height	86 mm

### Environment

Standards	BS 7288
IP degree of protection	IP20

### Offer Sustainability

EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.