

ARCA 203015W



Sample photo

Order symbol: ARCA 203015W
Product nbr: 8120140
Description: Cabinet, PC
Remarks: Cover with window, 1-point locking

EAN: 6418074080110
EI. number:
 Finland: 3423216
 Electric No. 8212091964
 Denmark:
 Electric No. Sweden: 2500137

Including: Cabinet base, door with PUR gasket, mounting plate, screws for mounting plate. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. Door guide included.

Dimensions:	Length	Width	Height	Accessories:
mm:	200	300	150	MPP ARCA 2030
inch:	7.9	11.8	5.9	MPMP ARCA 3020

Materials:

Material:	Polycarbonate
Base colour:	RAL 7035 -light grey
Cover colour:	RAL 7035 -light grey
Gasket material:	Polyurethane

Temperatures:

Temperature °C (short term):	-40 ... 120 °C
Temperature °C (continuous):	-40 ... 80 °C
Temperature °F (short term):	-40 ... 250 °F
Temperature °F (continuous):	-40 ... 175 °F

Accessories:

MPS ARCA 3020	Mounting plate (250x150x2 mm)
---------------	-------------------------------

MPP ARCA 2030	Mounting plate perforated (250x150x2 mm - 26x11 mm)
MPMP ARCA 3020	Mounting plate multiperforated (250x150x2 mm - □3.6 mm)
MPX ARCA 3020	Mounting plate (250x150 mm)
DRS ARCA 203015	DIN rail frame set
IDS ARCA 2030	Inner door set
PMK ARCA 30	Pole mounting kit
RCS ARCA 2030	Rain canopy set
SBK ARCA 20	Support bar kit
SBK ARCA 30	Support bar kit

Rating:

Ingress Protection (EN 60529):	IP65
Impact Resistance (EN 62262):	IK08
Electrical insulation:	Totally insulated
Halogen free (DIN/VDE 0472, Part 815):	1
Flammability Rating:	UL 94 5VA
Glow Wire Test (IEC 695-2-1) °C:	960
NEMA Class:	NEMA 4, 4X, 12 and 13

Certificates:
SGS Fimko

