

ARCA 302015W



Sample photo

Order symbol: ARCA 302015W
Product nbr: 8120122
Description: Cabinet, PC
Remarks: Cover with window, 1-point locking

EAN: 6418074079916
EI. number:
 Finland: 3423190
 Electric No. 8212091786
 Denmark:
 Electric No. Sweden: 2500138

Including: Cabinet base, door with PUR gasket, mounting plate, screws for mounting plate. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. Door guide included.

| Dimensions: | | | | Accessories: | |
|-------------------------------------|-------------------------------|-------|--------|--|---|
| | Length | Width | Height | | |
| mm: | 300 | 200 | 150 | MPP ARCA 3020 | Mounting plate perforated (250x150x2 mm - 26x11 mm) |
| inch: | 11.8 | 7.9 | 5.9 | MPMP ARCA 3020 | Mounting plate multiperforated (250x150x2 mm - □3.6 mm) |
| Materials: | | | | MPX ARCA 3020 | Mounting plate (250x150 mm) |
| Material: | Polycarbonate | | | DRS ARCA 302015 | DIN rail frame set |
| Base colour: | RAL 7035 -light grey | | | DRS ARCA 302021 | DIN rail frame set |
| Cover colour: | RAL 7035 -light grey | | | IDS ARCA 3020 | Inner door set |
| Gasket material: | Polyurethane | | | PMK ARCA 20 | Pole mounting kit |
| Temperatures: | | | | RCS ARCA 3020 | Rain canopy set |
| Temperature °C (short term): | -40 ... 120 °C | | | SBK ARCA 20 | Support bar kit |
| Temperature °C (continuous): | -40 ... 80 °C | | | SBK ARCA 30 | Support bar kit |
| Temperature °F (short term): | -40 ... 250 °F | | | Rating: | |
| Temperature °F (continuous): | -40 ... 175 °F | | | Ingress Protection (EN 60529): IP65 | |
| Accessories: | | | | Impact Resistance (EN 62262): IK08 | |
| MPS ARCA 3020 | Mounting plate (250x150x2 mm) | | | Electrical insulation: Totally insulated | |
| | | | | Halogen free (DIN/VDE 0472, Part 815): 1 | |
| | | | | Flammability Rating: UL 94 5VA | |
| | | | | Glow Wire Test (IEC 695-2-1) °C: 960 | |
| | | | | NEMA Class: NEMA 4, 4X, 12 and 13 | |
| | | | | Certificates: | |
| | | | | SGS Fimko | |

