

ARCA 403015W

Order symbol: ARCA 403015W
Product nbr: 8120126
Description: Cabinet, PC
Remarks: Cover with window, 2-point locking

EAN: 6418074079954
EI. number:
 Finland: 3423199
 Electric No. 8212091825
 Denmark:
 Electric No. Sweden: 2500140

Including: Cabinet base, door with PUR gasket, mounting plate, screws for mounting plate. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. Door guide included.

Dimensions:			Accessories:		
Length	Width	Height			
mm:	400	300	150	MPP ARCA 4030	Mounting plate perforated (350x250x2 mm - 26x11 mm)
inch:	15.7	11.8	5.9	MPMP ARCA 4030	Mounting plate multiperforated (350x250x2 mm - □3.6 mm)
Materials:			MPX ARCA 4030	Mounting plate (350x250 mm)	
Material:	Polycarbonate		DRS ARCA 403015	DIN rail frame set	
Base colour:	RAL 7035 -light grey		IDS ARCA 4030	Inner door set	
Cover colour:	RAL 7035 -light grey		PMK ARCA 30	Pole mounting kit	
Gasket material:	Polyurethane		RCS ARCA 4030	Rain canopy set	
Temperatures:			SBK ARCA 30	Support bar kit	
Temperature °C (short term):	-40 ... 120 °C		SBK ARCA 40	Support bar kit	
Temperature °C (continuous):	-40 ... 80 °C		DSP ARCA VLS	Door stopper ARCA, vertical, left, small	
Temperature °F (short term):	-40 ... 250 °F		DSP ARCA VRS	Door stopper ARCA, vertical, right, small	
Temperature °F (continuous):	-40 ... 175 °F		Rating:		
Accessories:			Ingress Protection (EN 60529): IP65		
MPS ARCA 4030	Mounting plate (350x250x2 mm)		Impact Resistance (EN 62262): IK08		
			Electrical insulation: Totally insulated		
			Halogen free (DIN/VDE 0472, Part 815): 1		
			Flammability Rating: UL 94 5VA		
			Glow Wire Test (IEC 695-2-1) °C: 960		
			NEMA Class: NEMA 4, 4X, 12 and 13		
			Certificates:		
			SGS Fimko		

