

**ARCA 604021**

**Order symbol:** ARCA 604021  
**Product nbr:** 8120012  
**Description:** Cabinet, PC  
**Remarks:** 2-point locking

**EAN:** 6418074079237  
**EI. number:**  
 Finland: 3423100  
 Electric No. 8212091100  
 Denmark:  
 Electric No. Sweden: 2500118



Sample photo

Including: Cabinet base, door with PUR gasket, mounting plate, screws for mounting plate. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. F versions with flange opening (including gasket and screws). Door guide included.

| Dimensions:                         | Length               | Width | Height | Accessories:    |   |
|-------------------------------------|----------------------|-------|--------|-----------------|---|
| mm:                                 | 600                  | 400   | 210    | MPP ARCA 6040   | Mounting plate perforated (550x350x2 mm - 26x11 mm)     |
| inch:                               | 23.6                 | 15.7  | 8.3    | MPMP ARCA 6040  | Mounting plate multiperforated (550x350x2 mm - □3.6 mm) |
| Materials:                          |                      |       |        | MPX ARCA 6040   | Mounting plate (550x350 mm)                             |
| <b>Material:</b>                    | Polycarbonate        |       |        | DRS ARCA 604021 | DIN rail frame set                                      |
| <b>Base colour:</b>                 | RAL 7035 -light grey |       |        | DRS ARCA 604030 | DIN rail frame set                                      |
| <b>Cover colour:</b>                | RAL 7035 -light grey |       |        | IDS ARCA 6040   | Inner door set  |
| <b>Gasket material:</b>             | Polyurethane         |       |        | PMK ARCA 40     | Pole mounting kit                                       |
| Temperatures:                       |                      |       |        | RCS ARCA 6040   | Rain canopy set   |
| <b>Temperature °C (short term):</b> | -40 ... 120 °C       |       |        | SBK ARCA 40     | Support bar kit   |
| <b>Temperature °C (continuous):</b> | -40 ... 80 °C        |       |        | SBK ARCA 60     | Support bar kit   |
| <b>Temperature °F (short term):</b> | -40 ... 250 °F       |       |        | DSP ARCA VLS    | Door stopper ARCA, vertical, left, small                |
| <b>Temperature °F (continuous):</b> | -40 ... 175 °F       |       |        | DSP ARCA VRS    | Door stopper ARCA, vertical, right, small               |

| Accessories:  |                               |
|---------------|-------------------------------|
| MPS ARCA 6040 | Mounting plate (550x350x2 mm) |

**Rating:**  
 Ingress Protection (EN 60529): IP66  
 Impact Resistance (EN 62262): IK10 +35°C /IK08 -25°C  
 Electrical insulation: Totally insulated  
 Halogen free (DIN/VDE 0472, Part 815): 1  
 UV resistance: UL 508  
 Flammability Rating: UL 94 5VA  
 Glow Wire Test (IEC 695-2-1) °C: 960

**Certificates:**

SGS Fimko  
 Gost R

