

**TEMPO TPC 191209T**



**Order symbol:** TPC 191209T  
**Product nbr:** 5824005  
**Description:** Enclosure, PC  
**Remarks:** Clear transparent cover

**EAN:** 6418074048646  
**EI. number:**  
**Finland:**

Including: Base with PUR gasket and screws for mounting plate/DIN-rail, cover with polyamide cover screws and plastic hinges.

Sample photo

Dimensions:		Length	Width	Height	Accessories:	
mm:		187	122	90	MIV 10	DIN-35 Mounting rail
inch:		7.4	4.8	3.5	DH-3	DIN-35 Mounting rail
					FP 10674	
Materials:				Rating:		
<b>Material:</b>	Polycarbonate			Ingress Protection (EN 60529): IP65		
<b>Base colour:</b>	RAL 7035 -light grey			Impact Resistance (EN 62262): IK07/IK08		
<b>Cover screws material:</b>	Polyamide			Electrical insulation: Totally insulated		
<b>Cover colour:</b>	RAL 7035 -light grey			Halogen free (DIN/VDE 0472, Part 815): 1		
<b>Cover screws colour:</b>	Grey			Flammability Rating: UL 746C 5"		
<b>Gasket material:</b>	Polyurethane			Glow Wire Test (IEC 695-2-1) °C: 960		
				NEMA Class: NEMA 1, 4, 4X, 12		
Temperatures:				Certificates:		
<b>Temperature °C (short term):</b>	-40 ... 120 °C			SGS Fimko		
<b>Temperature °C (continuous):</b>	-40 ... 80 °C					
<b>Temperature °F (short term):</b>	-40 ... 250 °F					
<b>Temperature °F (continuous):</b>	-40 ... 175 °F					
Accessories:						
MP 1912	Mounting plate					

