



KRYOS³ - GSV20



CODICE - CODE - ARTIKELNUMMER - CODIGO	M.U.	GSF20	GSV2000220	GSV2000203	GSV2000211
Portata Aria - Fan Flow - Luftmenge - Caudal Aire Ventil GSV	m ³ /h	--	108	108	108
UL		•	•	•	•
Portata Aria - Fan Flow - Luftmenge - Caudal Aire Ventil GSV+GSF20/GSF25	m ³ /h	--	75/88	75/88	75/88
Alimentazione - Power Supply - Spannungsversorgung - Alimentación Eléctrica	V-ph-Hz	--	230-1-50/60	115-1-50/60	24 VDC
Altezza/Larghezza/Profondità - Height/Width/depth - Höhe/Breite/Tiefe - Altura/Ancho/Profundidad (H x W x D)	mm	204x204x33,5	204x204x98	204x204x98	204x204x98
Potenza Assorbita - Power Absorbed - Leistungsaufnahme - Potencia Absorbida	W	--	22/22	22/24,5	8.1
Corrente Assorbita - Absorbed Current - Stromaufnahme - Corriente Absorbida	A	--	0.14/0.14	0.26/0.29	0.335
Fusibile T - Pre-Fuse T - Absicherung T - Elemento previo de Fusibile T	A	--	0.5	0.5	1
Limiti di Temperatura - Temperature Limits - Temperaturbereich - Limites Temperatura	°C	--	-10/+70*	-10/+70*	-10/+70*
Grado di Protezione - Protection Degree - Schutzgrad - Protección	IP/Nema	54/12	54/12	54/12	54/12
Rumorosità - Noise Level - Geräuschpegel - Nivel de ruido	dB(A)	--	49	49	48

*+55°C UL

