


Insulating modular boxes

Accessories

Fixing



| Characteristics | Wall-fixing lugs | | Post-fixing device | | Plastic carrying handle |
|---------------------------|------------------------------|-----------------|---|---|-------------------------|
| Material | Passivated zinc-coated steel | Stainless-steel | - | | Plastic |
| Ingress protection rating | - | | - | | IP43 |
| Supply | Set of 4 lugs and fixings | | Contains all the elements required for mounting on a post | | - |
| | References | | For installation on a surface with dimensions (mm) | References | Reference |
| | NSYPF27N | NSYPF27X | 270 360 540 | NSYFSP27270 NSYFSP27360 NSYFSP27540 | NSYATM27 |
| | | | | | |

Coupling



| Characteristics | Coupling frames (3) | | | Side plates (3) | | Box coupling unit piece | |
|---------------------------|---|---------------------|---------------------------|------------------------------|-------------------------|--|---------------------|
| | Use the boxes dimensional drawings to identify what coupling frame you need. Consider the sides and surfaces you will join. | | | - | | For coupling 2, 3 or 4 boxes, with optional wall-mounting. | |
| Ingress protection rating | <ul style="list-style-type: none"> ■ Frame with full opening: IP65 between enclosures ■ Frame with partial opening: IP44 between enclosures | | | IP65 | | - | |
| Supply | - | | | - | | To be ordered in multiples of 25 | |
| | References | | | | | For coupling (2) | |
| | For surfaces (mm) | Opening (mm) | Full-opening frame | Partial-opening frame | Side plates (mm) | 2 boxes | 3 or 4 boxes |
| | 180 | 110 | NSYUM27180 | - | - | - | - |
| | 270 | 200 | NSYUM27270 | NSYUCC270 (1) | 200 | NSYTL27270G | - |
| | 360 | 290 | NSYUM27360 | NSYUCC360 (1) | 290 | NSYTL27360G | - |
| | - | - | - | - | - | NSYPS2C27 | NSYPS4C27 |
| | | | | | | | |

(1) References by unit. Order by multiples of 10 units (10, 20, 30, etc.).

(2) M6 x 8 screw with cylindrical head.

(3) Not UL certified