



Sample photo

Order symbol: PC 050705
Product nbr: 7032520
Description: Enclosure, PC
Remarks: Grey cover

EAN: 6418074003607
El. number:
 Finland 3423424
 Denmark 8212002526
 Italy 7301010
 Sweden 2536105

Including: Base with screws for mounting plate/DIN-rail, cover with PUR gasket and stainless steel cover screws.

Dimensions:		L	W	H	Rating:
mm:		50	65	45	Ingress Protection (EN 60529): IP 66/67
inch:		2	2.6	1.8	Impact Resistance (EN 50102): IK 08/07
Materials:					
Material:		PC			
Base colour:		RAL 7035			
Cover colour:		RAL 7035			
Cover screws material:		Stainless steel			
Gasket material:		Polyurethane			
Temperatures:					
Short term:		-40 ... 120 °C			
Continuous:		-40 ... 80 °C			
Short term:		-40 ... 250 °F			
Continuous:		-40 ... 175 °F			
Accessories:					
TM 0505		Mounting plate			
TM 0507		Mounting plate			
TRM 0507		DIN-15 Mounting rail			
Electrical insulation:		Totally insulated			
Halogen free (DIN/VDE 0472, Part 815):		Yes			
UV resistance:		UL 508			
Flammability Rating (UL 746 C 5):		UL 94 5V			
Glow Wire Test (IEC 695-2-1) °C:		960			
NEMA Class:		NEMA 1, 4, 4X, 12, 13			
Certificates:					
		Underwriters Laboratories			
		Fimko			
		Europe EN 50298 1998			
		UL Canada			
		Gost R			

