



Sample photo

**Order symbol:** PC 121210  
**Product nbr:** 7032680  
**Description:** Enclosure, PC  
**Remarks:** Grey cover

**EAN:** 6418074003652  
**EI. number:**  
 Finland 3423434  
 Denmark 8212002762  
 Italy 7301035  
 Sweden 2536121

**Including:** Base with screws for mounting plate/DIN-rail, cover with PUR gasket and stainless steel cover screws.

Dimensions:		L	W	H	Rating:
mm:		120	122	95	<b>Ingress Protection (EN 60529):</b> IP 66/67
inch:		4.7	4.8	3.7	<b>Impact Resistance (EN 50102):</b> IK 08/07
Materials:					<b>Electrical insulation:</b> Totally insulated
<b>Material:</b>		PC			<b>Halogen free (DIN/VDE 0472, Part 815):</b> Yes
<b>Base colour:</b>		RAL 7035			<b>UV resistance:</b> UL 508
<b>Cover colour:</b>		RAL 7035			<b>Flammability Rating (UL 746 C 5):</b> UL 94 5V
<b>Cover screws material:</b>		Stainless steel			<b>Glow Wire Test (IEC 695-2-1) °C:</b> 960
<b>Gasket material:</b>		Polyurethane			<b>NEMA Class:</b> NEMA 1, 4, 4X, 12, 13
Temperatures:					Certificates:
<b>Short term:</b>		-40 ... 120 °C			<b>Underwriters Laboratories</b>
<b>Continuous:</b>		-40 ... 80 °C			<b>Fimko</b>
<b>Short term:</b>		-40 ... 250 °F			<b>Europe EN 50298 1998</b>
<b>Continuous:</b>		-40 ... 175 °F			<b>UL Canada</b>
Accessories:					<b>Gost R</b>
TM 1212		Mounting plate			
TRM 0812		DIN-15 Mounting rail			
TRM 1212		DIN-15 Mounting rail			
TRH 1212		DIN-35 Mounting rail			

