Product datasheet Characteristics



NSYPLA1276G

Floor standing enclosure polyester vers.PLA completely sealed 1250x750x420 IP65



Available from the UK's premier enclosure distributor, iLECSYS Ltd, 01844 397300 sales@ilecsys.co.uk

iLECSYS have in-house capabilities to accurately machine enclosures of all sizes and materials.

IΛ/	าล	ın
ıv	ıu	

	<u></u>
Thalassa	. <u></u>
Thalassa PLA	9
Multi-purpose	<u>u</u>
Suitable enclosure	٠ <u>۲</u>
PLA	
1250 mm	
750 mm	ў ‡
620 mm	, <u>+</u>
Floor-standing	eigen Alike
1 top part 1 bottom part 2 side part 1 rear panel 1 door	ining suitability or s
	Thalassa PLA Multi-purpose Suitable enclosure PLA 1250 mm 750 mm 620 mm Floor-standing 1 top part 1 bottom part 2 side part 1 rear panel

Complementary

Complementary		7
Body type	Sealed top and bottom part assembled with side parts	
Door type	Plain front	
Number of doors	1 door(s)	
Door opening side	Reversible (120 °)	
Lock type	4 points lock, 5 mm double-bar	
Accessibility for operation	Front Rear	a cubatr
Removable parts	Door by hinges Rear panel by fixing element	
Material	Polyester reinforced with fibreglass	<u></u>
Colour	Grey (RAL 7035)	. <u>.</u>
Standards	IEC 62208 UL 508 A	
NEMA degree of protection	NEMA 3 NEMA 3S NEMA 2 NEMA 4/4X NEMA 5	olamar This door

	NEMA 3R NEMA 3X NEMA 12 NEMA 1 NEMA 1
Product certifications	Veritas UL/cUL listed DNV Marine

Environment

IP degree of protection	IP65 conforming to IEC 60529 (completely sealed)
IK degree of protection	IK10 conforming to IEC 62262 (plain door)
Fire resistance	960 °C conforming to IEC 62208
Ambient air temperature for storage	-3590 °C

Offer Sustainability

REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
hina RoHS Regulation Download RoHS China Declaration Product out of China RoHS scope. Substance declaration for your information		

Contractual warranty

Contraction Warranty	
Warranty	18 months