
Product datasheet Characteristics

NSYPLA15103G

Floor standing enclosure polyester vers.PLA completely sealed 1500x1000x320 IP65









Available from the UK's premier enclosure distributor, iLECSYS Ltd, 01844 397300 sales@ilecsys.co.uk

iLECSYS have in-house capabilities to accurately machine enclosures of all sizes and materials.

Main

Main		¥
Range	Thalassa	-
Product name	Thalassa PLA	
Enclosure type	Multi-purpose	.
Product or component type	Suitable enclosure	, i
Version	PLA	
Nominal height	1500 mm	
Nominal width	1000 mm	
Nominal depth	320 mm	
Enclosure mounting	Floor-standing	
Device composition	1 top part 1 bottom part 2 side part 2 door 2 rear panel	

Complementary

Body type	Sealed top and bottom part assembled with side parts	
Door type	Plain front	
Number of doors	2 door(s)	
Door opening side	Right and left (120 °)	
Lock type	4 points lock, 5 mm double-bar	
Accessibility for operation	Rear Front	
Removable parts	Door by hinges Rear panel by fixing element	
Material	Polyester reinforced with fibreglass	
Colour	Grey (RAL 7035)	
Standards	UL 508 A IEC 62208	<u>و</u> ت ت ت

NEMA degree of protection	NEMA 12 NEMA 13 NEMA 2 NEMA 1
Product certifications	DNV Marine UL/cUL listed Veritas

Environment

IP degree of protection	IP65 conforming to IEC 60529 (completely sealed)	
IK degree of protection	IK10 conforming to IEC 62262 (plain door)	
Fire resistance 960 °C conforming to IEC 62208		
Ambient air temperature for storage -3590 °C		

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	Download RoHS China Declaration Product out of China RoHS scope. Substance declaration for your information	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	

Contractual warranty

Warranty	18 months	