
Product datasheet Characteristics

NSYS3D10825P

Spacial S3D plain door with mount.plate. H1000xW800xD250 IP66 IK10 RAL7035.





Main

Range Spacial Product name Spacial S3D Application Multi-purpose Category Compact enclosure Enclosure nominal height 1000 mm Enclosure nominal width 800 mm Enclosure nominal depth 250 mm Door type Plain Mounting plate description Plain Type of gland plate Standard Installation accessory type Wall-mounting Device composition 1 body 2 cable gland plate 1 mounting plate 1 door with lock	Mairi		
Application Multi-purpose Category Compact enclosure Enclosure nominal height 1000 mm Enclosure nominal width 800 mm Enclosure nominal depth 250 mm Door type Plain Mounting plate description Plain Type of gland plate Standard Installation accessory type Wall-mounting Device composition 1 body 2 cable gland plate 1 mounting plate 1 mounting plate	Range	Spacial	
Category Compact enclosure Enclosure nominal height 1000 mm Enclosure nominal width 800 mm Enclosure nominal depth 250 mm Door type Plain Mounting plate description Plain Type of gland plate Standard Installation accessory type Wall-mounting Device composition 1 body 2 cable gland plate 1 mounting plate	Product name	Spacial S3D	
Enclosure nominal height 1000 mm Enclosure nominal width 800 mm Enclosure nominal depth 250 mm Door type Plain Mounting plate description Plain Type of gland plate Standard Installation accessory type Wall-mounting Device composition 1 body 2 cable gland plate 1 mounting plate	Application	Multi-purpose	
Enclosure nominal width 800 mm Enclosure nominal depth 250 mm Door type Plain Mounting plate description Plain Type of gland plate Standard Installation accessory type Wall-mounting Device composition 1 body 2 cable gland plate 1 mounting plate	Category	Compact enclosure	
Enclosure nominal depth 250 mm Door type Plain Mounting plate description Plain Type of gland plate Standard Installation accessory type Wall-mounting Device composition 1 body 2 cable gland plate 1 mounting plate	Enclosure nominal height	1000 mm	
Door type Plain Mounting plate description Plain Type of gland plate Standard Installation accessory type Wall-mounting Device composition 1 body 2 cable gland plate 1 mounting plate	Enclosure nominal width	800 mm	
Mounting plate description Plain Type of gland plate Standard Installation accessory type Wall-mounting Device composition 1 body 2 cable gland plate 1 mounting plate	Enclosure nominal depth	250 mm	
Type of gland plate Standard Installation accessory type Wall-mounting Device composition 1 body 2 cable gland plate 1 mounting plate	Door type	Plain	
Installation accessory type Wall-mounting Device composition 1 body 2 cable gland plate 1 mounting plate	Mounting plate description	Plain	
Device composition 1 body 2 cable gland plate 1 mounting plate	Type of gland plate	Standard	
2 cable gland plate 1 mounting plate	Installation accessory type	Wall-mounting	
	Device composition	2 cable gland plate 1 mounting plate	

Complementary

		:
Body type	Single piece body Gutter-shaped front rail double sheet thickness	
Number of doors	Front face: 1 door(s)	-
Door opening side	Reversible (120 °)	
Lock type	3 points lock, 3 mm double-bar	
Accessibility for operation	Front	
Removable parts	Door by hinges Cable gland plate by screws Mounting plate by fixing element	
Material	Enclosure: steel Mounting plate: galvanised steel	F
Surface finish	Enclosure: epoxy-polyester powder	

Colour	Enclosure: grey (RAL 7035)
Standards	IEC 62208
Product certifications	LR
	UL
	GL
	CUL
	DNV
	BV
Product weight	49 kg

Environment

IP degree of protection	IP66 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	Download RoHS China Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	

Contractual warranty

on the dotter. The first of the		
Warranty	18 months	