
## **Product datasheet** Characteristics

# NSYS3D12640P

Spacial S3D plain door with mount.plate. H1200xW600xD400 IP66 IK10 RAL7035.





## Main

Main		4
Range	Spacial	
Product name	Spacial S3D	
Application	Multi-purpose	\$
Category	Compact enclosure	1
Enclosure nominal height	1200 mm	
Enclosure nominal width	600 mm	
Enclosure nominal depth	400 mm	<u></u>
Door type	Plain	
Mounting plate description	Plain	
Type of gland plate	Standard	
Installation accessory type	Wall-mounting	
Device composition	1 body 1 mounting plate 1 door with lock 1 cable gland plate	5

#### Complementary

Body type	Single piece body Gutter-shaped front rail double sheet thickness	
Number of doors	Front face: 1 door(s)	
Door opening side	Reversible (120 °)	
Lock type	3 points lock, 3 mm double-bar	
Accessibility for operation	Front	
Removable parts	Door by hinges Cable gland plate by screws Mounting plate by fixing element	o documents
Material	Enclosure: steel Mounting plate: galvanised steel	E. S. C. S.
Surface finish	Enclosure: epoxy-polyester powder	

1

Life Is On Schneider

Colour	Enclosure: grey (RAL 7035)
Standards	IEC 62208
Product certifications	BV CUL LR GL DNV
Product weight	UL

#### Environment

IP degree of protection	IP66 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262

### Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	Download RoHS China Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	

#### Contractual warranty

Warranty	18 months	