
Product datasheet Characteristics

NSYS3D5525P

Spacial S3D plain door with mount.plate. H500xW500xD250 IP66 IK10 RAL7035.





Main

Iviairi		
Range	Spacial	
Product name	Spacial S3D	
Application	Multi-purpose	
Category	Compact enclosure	
Enclosure nominal height	500 mm	
Enclosure nominal width	500 mm	
Enclosure nominal depth	250 mm	
Door type	Plain	
Mounting plate description	Plain	
Type of gland plate	Standard	
Installation accessory type	Wall-mounting	
Device composition	1 body 1 mounting plate 1 door with lock 1 cable gland plate	
	- .	

Complementary

		*
Body type	Single piece body Gutter-shaped front rail double sheet thickness	
Number of doors	Front face: 1 door(s)	
Door opening side	Reversible (120 °)	
Lock type	3 mm double-bar lock	
Accessibility for operation	Front	
Removable parts	Door by hinges Cable gland plate by screws Mounting plate by fixing element	
Material	Enclosure: steel Mounting plate: galvanised steel	f
Surface finish	Enclosure: epoxy-polyester powder	

Colour	Enclosure: grey (RAL 7035)
Standards	IEC 62208
Product certifications	UL CUL LR
	BV GL DNV
Product weight	15 kg

Environment

IP degree of protection	IP66 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	Download RoHS China Declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	

Contractual warranty

on the dotter. The first of the		
Warranty	18 months	